

SANYO

No.1845C

**LA3605**

Monolithic Linear IC

7-BAND GRAPHIC EQUALIZER

Applications

- Portable component stereos, radio-cassette recorders, tape recorders, car stereos.

Features

- One OP amp on chip.
- 7-band graphic equalizer for one channel can be formed easily by externally connecting capacitors and variable resistors which fix f_0 (resonance frequency).
- Series connection of two LA3605's makes multiband available.
- Highly stable to capacitive load.

Maximum Ratings at $T_a=25^\circ\text{C}$

		unit
Maximum Supply Voltage	$V_{CC\max}$	20 V
Allowable Power Dissipation	P_{dmax}	300 mW
Operating Temperature	T_{opg}	-20 to +75 $^\circ\text{C}$
Storage Temperature	T_{stg}	-40 to +125 $^\circ\text{C}$



Operating Conditions at $T_a=25^\circ\text{C}$

		unit
Recommended Supply Voltage	V_{CC}	8 V
Operating Voltage Range	V_{CCOP}	5 to 15 V

Operating Characteristics at $T_a=25^\circ\text{C}, V_{CC}=8\text{V}, R_L=10\text{kohms}, R_g=600\text{ohms}$, See specified test circuit.

			min	typ	max	unit
Quiescent Current	I_{CC0}	Quiescent	7	9	mA	
Voltage Gain	VG	$f=1\text{kHz}, V_{in}=-10\text{dB}$ at all flat mode	-3.8	-0.8	2.2	dB
Boost Amount	BOOST	$f=60\text{Hz}$ [$V_{o}=-10\text{dB}$ is taken]	8	10	12	dB
		$f=150\text{Hz}$ as 0dB at all	8	10	12	dB
		$f=400\text{Hz}$ flat mode at $f=1\text{kHz}$.	8	10	12	dB
			8	10	12	dB

Continued on next page.

**Case Outline 3021B-D20SIC**
(unit:mm)

Specifications and information herein are subject to change without notice.

SANYO Electric Co.,Ltd. Semiconductor Overseas Marketing Div.
15-13, 6 chome, Sotokanda, Chiyoda-ku, TOKYO 101 JAPAN


Continued from preceding page.

Boost Amount	BOOST	f=2.5kHz	8	10	12	dB	
Cut Amount	CUT	f=6kHz f=15kHz f=60Hz f=150Hz f=400Hz f=1kHz f=2.5kHz f=6kHz f=15kHz	V _O =-10dB is taken as 0dB at all frequencies. flat mode at f=1kHz.	8	10	12	dB
Total Harmonic Distortion THD		All FLAT, V _O =1.0V, f=1kHz	8	10	12	dB	
Output Noise Voltage V _{NO}		All FLAT, input short, B.P.F, 10Hz to 30kHz	0.04	0.1	1	%	
			3	20	3	uV	

Test Method: V_{CC}=8V, R_L=10kohms, R_G=600ohms


Item	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	Conditions
J _{cc0}	1	F	F	F	F	F	F	F	2	1	
V _G	2	F	F	F	F	F	F	F	1	1	f=1kHz, V _{IN} =-10dB
BOOST1	2	B	F	F	F	F	F	F	1	1	f=60Hz
BOOST2	2	F	B	F	F	F	F	F	1	1	f=150Hz
BOOST3	2	F	F	B	F	F	F	F	1	1	f=400Hz
BOOST4	2	F	F	F	B	F	F	F	1	1	f=1kHz
BOOST5	2	F	F	F	F	B	F	F	1	1	f=2.5kHz
BOOST6	2	F	F	F	F	F	B	F	1	1	f=6kHz
BOOST7	2	F	F	F	F	F	F	B	1	1	f=15kHz
CUT1	2	C		F	F	F	F	F	1	1	f=60Hz
CUT2	2	F	C	F	F	F	F	F	1	1	f=150Hz
CUT3	2	F	F	C	F	F	F	F	1	1	f=400Hz
CUT4	2	F	F	F	C	F	F	F	1	1	f=1kHz
CUT5	2	F	F	F	C	F	F	F	1	1	f=2.5kHz
CUT6	2	F	F	F	F	C	F	F	1	1	f=6kHz
CUT7	2	F	F	F	F	F	C	F	1	1	f=15kHz
THD	2	F	F	F	F	F	F	F	1	1	f=1kHz, V _O =1.0V
V _{NO}	2	F	F	F	F	F	F	F	2	2	

Test Circuit




LA3605


Equivalent Circuit Block Diagram



Sample Application Circuit



Sample Printed Circuit Pattern



f_0 (resonance frequency)

In the sample application circuit, f_0 for each of 7 bands is set as follows:

$f_0 = 60\text{Hz}, 150\text{Hz}, 400\text{Hz}, 1\text{kHz}, 2.5\text{kHz}, 6\text{kHz}, 15\text{kHz}$

f_0 is calculated using the following formula.

$$f_0 = \frac{1}{2\pi\sqrt{C_1 \cdot C_2 \cdot R_1 \cdot R_2}}$$

Q (quality factor)

Q is calculated using the following formula.

$$Q = \sqrt{\frac{C_1 \cdot R_2}{C_2 \cdot R_1}}$$

When Q is increased, the frequency band affected by the resonance circuit is narrowed and a clear distinction between this band and an adjacent band is provided, but the frequency response swells greatly at all boost mode and the peak of the composite frequency is lowered.

The above must be considered to fix C_1, C_2 .

Description of external parts

C_1, C_2 : Capacitors used to fix f_0 (resonance frequency)

C_3 : Input capacitor. Decreasing the capacitor value lowers the frequency response at low frequencies.



C_4 : Decoupling capacitor. Decreasing the capacitor value makes the effect of power supply stronger, whereby ripple is liable to occur.





C_5 : Power capacitor.

C_6 : Output capacitor. Decreasing the capacitor value lowers the frequency response at low frequencies.

Proper cares in using IC

- Maximum supply voltage $V_{CC\max} 20\text{V}$ must not be exceeded. The operating voltage is in the range of 5 to 15V.
- Application of power with the pin-to-pin spaces shorted causes breakdown or deterioration of the IC to occur. When mounting the IC on the board or applying power, make sure that the pin-to-pin spaces are not shorted with solder, etc.






DISCONTINUED

The application circuit diagrams and circuit constants herein are included as an example and provide no guarantees for designing equipment to be mass-produced.
The information herein is believed to be accurate and reliable. However, no responsibility is assumed by SANYO for its use, nor
for any infringements of patents or other rights of third parties which may result from its use.

LA3605



LED PRODUCTS