## National Semiconductor

#### **ADVANCE INFORMATION**

### LMC6772 Dual, LMC6774 Quad, Micro-Power Rail-To-Rail Input and Open Drain Output CMOS Comparator

#### **General Description**

The LMC6772/4 is an ultra low power dual/quad comparator with a maximum 10 μA/comparator power supply current. It is designed to operate over a wide range of supply voltages, from 2.7V to 15V. The LMC6772/4 has guaranteed specs at 2.7V to meet the demands of 3V digital systems.

The LMC6772/4 has an input common-mode voltage range which exceeds both rails. This is a significant advantage in low-voltage applications. The LMC6772/4 also features an open-drain output. This architecture is ideal for mixed supply voltage systems as an external resistor can be used to pull the output up to + 15V, regardless of the supply voltage.

A quiescent power consumption of 50  $\mu$ W/Amplifier (@Vs = 5V) makes the LMC6772/4 ideal for applications in portable phones and hand-held electronics. The ultra-low supply current is also independent of the power supply voltage. Guaranteed operation at 2.7V and rail-to-rail performance make the device ideal for battery-powered applications.

#### Features (Typical unless otherwise noted)


- Low power consumption
- Wide range of supply voltages
- $I_S = 10 \mu A/comp$ 2.7V to 15V
- Rail-to-Rail Input Common Mode Voltage Range
- Open-drain output stage
- Short circuit protection

- 40 mA
- Propagation delay (@V<sub>S</sub> = 5V, 100 mV overdrive) 5  $\mu$ s
- Refer to the LMC6762/4 datasheet for a device with similar specs and a push-pull output stage

#### **Applications**

- Laptop computers
- Mobile Phones
- Metering systems
- Hand-held electronics
- RC timers, Window Comparators, Multivibrators
- Alarm and monitoring circuits

#### **Connection Diagrams**



**Top View** 

TL/H/12347-1

# OUT B 1 2 0UT C 13 OUT C 14 OUT C 15 OUT B 1 15 OUT C 17 OUT C 17 OUT C 18 OUT D 18 OUT D 19 OUT D 19

**Top View** 

TL/	H/123	47-2

Package	Temperature Range Industrial, -40°C to +85°C	NSC Drawing	Transport Media
8-Pin Molded DIP	LMC6772AIN, LMC6772BIN	N08E	Rails
8-Pin Small Outline		MOBA	Rails
	LMC6772AIMX, LMC6772BIMX	MUSA	Tape and Reel
14-Pin Molded DIP	LMC6774AIN, LMC6774BIN	N14A	Rails
14-Pin Small Outline	LMC6774AIM, LMC6774BIM	─────────────────────────────────────	Rails
	LMC6774AIMX, LMC6774BIMX		Tape and Reel