

The specifications for the **LTC[®]1296xIS** are identical to those of the **LTC1296xCS** grades except that the (●) denotes a temperature range of -40°C to 85°C . For complete specifications, typical performance curves and applications information, please see the **LTC1293/LTC1294/LTC1296** data sheets.

 and LTC are registered trademarks and LT is a trademark of Linear Technology Corporation.

PACKAGE/ORDER INFORMATION

TOP VIEW		ORDER PART NUMBER
CH0	1	20 V _{CC}
CH1	2	19 SSO
CH2	3	18 CLK
CH3	4	17 CS
CH4	5	16 D _{OUT}
CH5	6	15 D _{IN}
CH6	7	14 REF ⁺
CH7	8	13 REF ⁻
COM	9	12 AGND
DGND	10	11 V ⁻
S PACKAGE 20-LEAD PLASTIC SOL $T_{JMAX} = 110^{\circ}\text{C}$, $\theta_{JA} = 150^{\circ}\text{C/W}$		LTC1296BCS LTC1296CCS LTC1296DCS LTC1296BIS LTC1296CIS LTC1296DIS

For further information regarding this specification notice contact:

Linear Technology Corporation
 1630 McCarthy Blvd.
 Milpitas, California 95035-7487
 Attn: Product Marketing Manager
 Phone: (408) 432-1900