

HEX INVERTER


S5404

N7404

S5404-A,F,W • N7404-A,F


DIGITAL 54/74 TTL SERIES

SCHEMATIC (each inverter)




PIN CONFIGURATIONS

W PACKAGE



A,F PACKAGE



NOTE: Component values shown are nominal.

RECOMMENDED OPERATING CONDITIONS

| | MIN | NOM | MAX | UNIT |
|--|------|-----|------|------|
| Supply Voltage V_{CC} : S5404 Circuits | 4.5 | 5 | 5.5 | V |
| N7404 Circuits | 4.75 | 5 | 5.25 | V |
| Normalized Fan-Out from Output, N | | | 10 | |
| Operating Free-Air Temperature Range, T_A : S5404 Circuits | -55 | 25 | 125 | °C |
| N7404 Circuits | 0 | 25 | 70 | °C |

ELECTRICAL CHARACTERISTICS (over recommended operating free-air temperature range unless otherwise noted)

| PARAMETER | TEST CONDITIONS* | MIN | TYP** | MAX | UNIT |
|--------------|--|--------------------|------------|------------|------|
| $V_{in(1)}$ | $V_{CC} = \text{MIN}$ | | 2 | | V |
| $V_{in(0)}$ | $V_{CC} = \text{MIN}$ | | | 0.8 | V |
| $V_{out(1)}$ | $V_{CC} = \text{MIN}$, $I_{load} = -400\mu\text{A}$ | | 2.4 | 3.3 | V |
| $V_{out(0)}$ | $V_{CC} = \text{MIN}$, $I_{sink} = 16\text{mA}$ | | 0.22 | 0.4 | V |
| $I_{in(0)}$ | $V_{CC} = \text{MAX}$, | | | -1.6 | mA |
| $I_{in(1)}$ | $V_{CC} = \text{MAX}$, $V_{CC} = \text{MAX}$, $V_{in} = 0.4\text{V}$ | | | 40 | μA |
| I_{OS} | $V_{CC} = \text{MAX}$ | $S5404$ $N7404$ | -20 -18 | -55 -55 | mA |
| | | | | 1 | mA |

SIGNETICS DIGITAL 54/74 TTL SERIES - S5404 • N7404

ELECTRICAL CHARACTERISTICS (Cont'd)

| PARAMETER | TEST CONDITIONS * | MIN | TYP | MAX | UNIT |
|---|---|-----|-----|-----|------|
| I _{CC(0)} Logical 0 level supply current | V _{CC} = MAX, V _{in} = 5V | | 18 | 33 | mA |
| I _{CC(1)} Logical 1 level supply current | V _{CC} = MAX, V _{in} = 0 | | 6 | 12 | mA |

SWITCHING CHARACTERISTICS, V_{CC} = 5V, T_A = 25°C, N = 10

| PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|--|-----|-----|-----|------|
| t _{pd0} Propagation delay time to logical 0 level | C _L = 15pF, R _L = 400Ω | | 8 | 15 | ns |
| t _{pd1} Propagation delay time to logical 1 level | C _L = 15pF, R _L = 400Ω | | 12 | 22 | ns |

* For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable device type.

** All typical values are at V_{CC} = 5V, T_A = 25°C.

† Not more than one output should be shorted at a time.