

SN74AXC8T245 8-Bit Dual-Supply Bus Transceiver With Configurable Voltage Translation and Tri-State Outputs

1 Features

- Qualified Fully Configurable Dual-Rail Design Allows Each Port to Operate With a Power Supply Range From 0.65 V to 3.6 V
- Operating Temperature From -40°C to $+125^{\circ}\text{C}$
- Multiple Direction Control Pins to Allow Simultaneous Up and Down Translation
- Up to 380 Mbps Support When Translating from 1.8 V to 3.3 V
- V_{CC} Isolation Feature to Effectively Isolate Both Buses in a Power-Down Scenario
- Partial Power-Down Mode to Limit Backflow Current in a Power-Down Scenario
- Compatible With SN74AVC8T245 and 74AVC8T245 Level Shifters
- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Protection Exceeds JESD 22
 - 8000-V Human-Body Model
 - 1000-V Charged-Device Model

2 Applications

- Enterprise and Communications
- Industrial
- Personal Electronics
- Wireless Infrastructure
- Building Automation
- Point of Sale

3 Description

The SN74AXC8T245 device is an 8-bit non-inverting bus transceiver that resolves voltage level mismatch between devices operating at the latest voltage nodes (0.7 V, 0.8 V, and 0.9 V) and devices operating at industry standard voltage nodes (1.8 V, 2.5 V, 3.3 V) and vice versa.

The device operates by using two independent power-supply rails (V_{CCA} and V_{CCB}) that operate as low as 0.65 V. Data pins A1 through A8 are designed to track V_{CCA} , which accepts any supply voltage from 0.65 V to 3.6 V. Data pins B1 through B8 are designed to track V_{CCB} , which accepts any supply voltage from 0.65 V to 3.6 V.

The SN74AXC8T245 device is designed for asynchronous communication between data buses. The device transmits data from the A bus to the B bus or from the B bus to the A bus, depending on the logic level of the direction-control inputs (DIR1 and DIR2). The output-enable (\overline{OE}) input is used to disable the outputs so the buses are effectively isolated.

The SN74AXC8T245 device is designed so the control pins (DIR and \overline{OE}) are referenced to V_{CCA} .

This device is fully specified for partial-power-down applications using I_{off} . The I_{off} circuitry disables the outputs when the device is powered down. This inhibits current backflow into the device which prevents damage to the device.

The V_{CC} isolation feature ensures that if either V_{CC} input supply is below 100 mV, all level shifter outputs are disabled and placed into a high-impedance state.

To ensure the high-impedance state of the level shifter I/Os during power up or power down, \overline{OE} should be tied to V_{CCA} through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

Device Information⁽¹⁾

PART NUMBER	PACKAGE	BODY SIZE (NOM)
SN74AXC8T245PW	TSSOP (24)	4.40 mm × 7.80 mm
SN74AXC8T245RHL	VQFN (24)	3.50 mm × 5.50 mm
SN74AXC8T245RJW ⁽²⁾	UQFN (24)	2.00 mm × 4.00 mm

(1) For all available packages, see the orderable addendum at the end of the data sheet.

(2) Package preview only.

Typical Application Schematic







Table of Contents

1	Features	1	8	Detailed Description	20
2	Applications	1	8.1	Overview	20
3	Description	1	8.2	Functional Block Diagram	20
4	Revision History	2	8.3	Feature Description	21
5	Pin Configuration and Functions	3	8.4	Device Functional Modes	21
6	Specifications	5	9	Application and Implementation	22
6.1	Absolute Maximum Ratings	5	9.1	Application Information	22
6.2	ESD Ratings	5	9.2	Typical Application	22
6.3	Recommended Operating Conditions	6	10	Power Supply Recommendations	24
6.4	Thermal Information	6	11	Layout	24
6.5	Electrical Characteristics	7	11.1	Layout Guidelines	24
6.6	Switching Characteristics, $V_{CCA} = 0.7\text{ V}$	8	11.2	Layout Example	24
6.7	Switching Characteristics, $V_{CCA} = 0.8\text{ V}$	9	12	Device and Documentation Support	25
6.8	Switching Characteristics, $V_{CCA} = 0.9\text{ V}$	10	12.1	Documentation Support	25
6.9	Switching Characteristics, $V_{CCA} = 1.2\text{ V}$	11	12.2	Receiving Notification of Documentation Updates	25
6.10	Switching Characteristics, $V_{CCA} = 1.5\text{ V}$	12	12.3	Community Resources	25
6.11	Switching Characteristics, $V_{CCA} = 1.8\text{ V}$	13	12.4	Trademarks	25
6.12	Switching Characteristics, $V_{CCA} = 2.5\text{ V}$	14	12.5	Electrostatic Discharge Caution	25
6.13	Switching Characteristics, $V_{CCA} = 3.3\text{ V}$	15	12.6	Glossary	25
6.14	Operating Characteristics: $T_A = 25^\circ\text{C}$	16	13	Mechanical, Packaging, and Orderable Information	25
7	Parameter Measurement Information	18			

4 Revision History

Changes from Revision Original (March 2018) to Revision A	Page
• Added RJW as a new package option (preview).	1

5 Pin Configuration and Functions



(1) Preview only.

SN74AXC8T245

SCES875 – MARCH 2018 – REVISED JULY 2018

www.ti.com
Pin Functions

PIN			I/O	DESCRIPTION
NAME	PW, RHL	RJW		
A1	3	2	I/O	Input/output A1. Referenced to V_{CCA} .
A2	4	3	I/O	Input/output A2. Referenced to V_{CCA} .
A3	5	4	I/O	Input/output A3. Referenced to V_{CCA} .
A4	6	5	I/O	Input/output A4. Referenced to V_{CCA} .
A5	7	6	I/O	Input/output A5. Referenced to V_{CCA} .
A6	8	7	I/O	Input/output A6. Referenced to V_{CCA} .
A7	9	8	I/O	Input/output A7. Referenced to V_{CCA} .
A8	10	9	I/O	Input/output A8. Referenced to V_{CCA} .
B1	21	20	I/O	Input/output B1. Referenced to V_{CCB} .
B2	20	19	I/O	Input/output B2. Referenced to V_{CCB} .
B3	19	18	I/O	Input/output B3. Referenced to V_{CCB} .
B4	18	17	I/O	Input/output B4. Referenced to V_{CCB} .
B5	17	16	I/O	Input/output B5. Referenced to V_{CCB} .
B6	16	15	I/O	Input/output B6. Referenced to V_{CCB} .
B7	15	14	I/O	Input/output B7. Referenced to V_{CCB} .
B8	14	13	I/O	Input/output B8. Referenced to V_{CCB} .
DIR1	2	1	I	Direction-control signal. Referenced to V_{CCA} .
DIR2	11	10	I	Direction-control signal when both V_{CCA} and $V_{CCB} \geq 1.4$ V. Referenced to V_{CCA} . Tie to GND to maintain backward compatibility with SN74AVC8T245 device.
GND	12	11	—	Ground
	13	12	—	Ground
\overline{OE}	22	21	I	Output Enable. Pull to GND to enable all outputs. Pull to V_{CCA} to place all outputs in high-impedance mode. Referenced to V_{CCA} .
V_{CCA}	1	24	—	A-port supply voltage. $0.65\text{ V} \leq V_{CCA} \leq 3.6\text{ V}$
V_{CCB}	23	22	—	B-port supply voltage. $0.65\text{ V} \leq V_{CCB} \leq 3.6\text{ V}$
	24	23	—	B-port supply voltage. $0.65\text{ V} \leq V_{CCB} \leq 3.6\text{ V}$

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)⁽¹⁾

		MIN	MAX	UNIT
Supply voltage, V_{CCA}		−0.5	4.2	V
Supply voltage, V_{CCB}		−0.5	4.2	V
Input voltage, V_I ⁽²⁾	I/O ports (A port)	−0.5	4.2	V
	I/O ports (B port)	−0.5	4.2	
	Control inputs	−0.5	4.2	
Voltage applied to any output in the high-impedance or power-off state, V_O ⁽²⁾	A port	−0.5	4.2	V
	B port	−0.5	4.2	
Voltage applied to any output in the high or low state, V_O ^{(2) (3)}	A port	−0.5	$V_{CCA} + 0.2$	V
	B port	−0.5	$V_{CCB} + 0.2$	
Input clamp current, I_{IK}	$V_I < 0$	−50		mA
Output clamp current, I_{OK}	$V_O < 0$	−50		mA
Continuous output current, I_O		−50	50	mA
Continuous current through V_{CCA} , V_{CCB} , or GND		−100	100	mA
Junction Temperature, T_J			150	°C
Storage temperature, T_{stg}		−65	150	°C

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input voltage and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.
- (3) The output positive-voltage rating may be exceeded up to 4.2 V maximum if the output current rating is observed.

6.2 ESD Ratings

		VALUE	UNIT
$V_{(ESD)}$ Electrostatic discharge	Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	±8000	V
	Charged-device model (CDM), per JEDEC specification JESD22-C101 ⁽²⁾	±1000	

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted) ⁽¹⁾⁽²⁾⁽³⁾

			MIN	MAX	UNIT
V _{CCA}	Supply voltage		0.65	3.6	V
V _{CCB}	Supply voltage		0.65	3.6	V
V _{IH}	High-level input voltage	Data inputs	V _{CCI} = 0.65 V - 0.75 V	V _{CCI} × 0.70	V
			V _{CCI} = 0.76 V - 1 V	V _{CCI} × 0.70	
			V _{CCI} = 1.1 V - 1.95 V	V _{CCI} × 0.65	
			V _{CCI} = 2.3 V - 2.7 V	1.6	
			V _{CCI} = 3 V - 3.6 V	2	
	Control inputs (DIR, \overline{OE}) Referenced to V _{CCA}		V _{CCA} = 0.65 V - 0.75 V	V _{CCA} × 0.70	
			V _{CCA} = 0.76 V - 1 V	V _{CCA} × 0.70	
			V _{CCA} = 1.1 V - 1.95 V	V _{CCA} × 0.65	
			V _{CCA} = 2.3 V - 2.7 V	1.6	
			V _{CCA} = 3 V - 3.6 V	2	
V _{IL}	Low-level input voltage	Data inputs	V _{CCI} = 0.65 V - 0.75 V	V _{CCI} × 0.30	V
			V _{CCI} = 0.76 V - 1 V	V _{CCI} × 0.30	
			V _{CCI} = 1.1 V - 1.95 V	V _{CCI} × 0.35	
			V _{CCI} = 2.3 V - 2.7 V	0.7	
			V _{CCI} = 3 V - 3.6 V	0.8	
	Control inputs (DIR, \overline{OE}) Referenced to V _{CCA}		V _{CCA} = 0.65 V - 0.75 V	V _{CCA} × 0.30	
			V _{CCA} = 0.76 V - 1 V	V _{CCA} × 0.30	
			V _{CCA} = 1.1 V - 1.95 V	V _{CCA} × 0.35	
			V _{CCA} = 2.3 V - 2.7 V	0.7	
			V _{CCA} = 3 V - 3.6 V	0.8	
V _I	Input voltage ⁽³⁾		0	3.6	V
V _O	Output voltage	Active state	0	V _{CCO} ⁽²⁾	V
		Tri-state	0	3.6	
Δt/Δv	Input transition rise or fall rate			10	ns/V
T _A	Operating free-air temperature		–40	125	°C

(1) V_{CCI} is the V_{CC} associated with the input port.

(2) V_{CCO} is the V_{CC} associated with the output port.

(3) All unused data inputs of the device must be held at V_{CCI} or GND to ensure proper device operation. See the [Implications of Slow or Floating CMOS Inputs](#) application report.

6.4 Thermal Information

THERMAL METRIC		SN74AXC8T245			UNIT
		PW (TSSOP)	RHL (VQFN)	RJW (UQFN)	
		24 PINS	24 PINS	24 PINS	
R _{θJA}	Junction-to-ambient thermal resistance	92.0	35.0	123.1	°C/W
R _{θJC(top)}	Junction-to-case (top) thermal resistance	29.3	39.9	65.0	°C/W
R _{θJB}	Junction-to-board thermal resistance	46.7	13.8	55.3	°C/W
ψ _{JT}	Junction-to-top characterization parameter	1.5	0.3	3.9	°C/W
ψ _{JB}	Junction-to-board characterization parameter	46.2	13.8	54.9	°C/W
R _{θJC(bot)}	Junction-to-case (bottom) thermal resistance	N/A	1.4	N/A	°C/W

6.5 Electrical Characteristics

Over recommended operating free-air temperature range (unless otherwise noted)⁽¹⁾

PARAMETER	TEST CONDITIONS	V _{CCA}	V _{CCB}	–40°C to 85°C			–40°C to 125°C			UNIT
				MIN	TYP ⁽²⁾	MAX	MIN	TYP ⁽²⁾	MAX	
V _{OH} High-level output voltage	V _I = V _{IH}	I _{OH} = –100 µA	0.7 V - 3.6 V	0.7 V - 3.6 V	V _{CCO} – 0.1		V _{CCO} – 0.1			V
		I _{OH} = –50 µA	0.65 V	0.65 V	0.55		0.55			
		I _{OH} = –200 µA	0.76 V	0.76 V	0.58		0.58			
		I _{OH} = –500 µA	0.85 V	0.85 V	0.65		0.65			
		I _{OH} = –3 mA	1.1 V	1.1 V	0.85		0.85			
		I _{OH} = –6 mA	1.4 V	1.4 V	1.05		1.05			
		I _{OH} = –8 mA	1.65 V	1.65 V	1.2		1.2			
		I _{OH} = –9 mA	2.3 V	2.3 V	1.75		1.75			
		I _{OH} = –12 mA	3 V	3 V	2.3		2.3			
V _{OL} Low-level output voltage	V _I = V _{IL}	I _{OL} = 100 µA	0.7 V - 3.6 V	0.7 V - 3.6 V					0.1	V
		I _{OL} = 50 µA	0.65 V	0.65 V					0.1	
		I _{OL} = 200 µA	0.76 V	0.76 V					0.18	
		I _{OL} = 500 µA	0.85 V	0.85 V					0.2	
		I _{OL} = 3 mA	1.1 V	1.1 V					0.25	
		I _{OL} = 6 mA	1.4 V	1.4 V					0.35	
		I _{OL} = 8 mA	1.65 V	1.65 V					0.45	
		I _{OL} = 9 mA	2.3 V	2.3 V					0.55	
		I _{OL} = 12 mA	3 V	3 V					0.7	
I _I Input leakage current	Control Inputs (DIR, $\overline{\text{OE}}$): V _I = V _{CCA} or GND	0.65 V - 3.6 V	0.65 V - 3.6 V	–0.5		0.5	–1		1	µA
I _{off} Partial power down current	A Port: V _I or V _O = 0 V - 3.6 V	0 V	0 V - 3.6 V	–4		4	–8		8	µA
	B Port: V _I or V _O = 0 V - 3.6 V	0 V - 3.6 V	0 V	–4		4	–8		8	
I _{OZ} High-impedance state output current	A Port: V _O = V _{CCO} or GND, V _I = V _{CCI} or GND, $\overline{\text{OE}}$ = V _{IH}	3.6 V	3.6 V	–4		4	–8		8	µA
	B Port: V _O = V _{CCO} or GND, V _I = V _{CCI} or GND, $\overline{\text{OE}}$ = V _{IH}	3.6 V	3.6 V	–4		4	–8		8	
I _{CCA} V _{CCA} supply current	V _I = V _{CCI} or GND, I _O = 0 mA	0.65 V - 3.6 V	0.65 V - 3.6 V			19			40	µA
		0 V	3.6 V	–2			–12			
		3.6 V	0 V			12			25	
I _{CCB} V _{CCB} supply current	V _I = V _{CCI} or GND, I _O = 0 mA	0.65 V - 3.6 V	0.65 V - 3.6 V			18			38	µA
		0 V	3.6 V			12			25	
		3.6 V	0 V	–2			–12			
I _{CCA} + I _{CCB} Combined supply current	V _I = V _{CCI} or GND, I _O = 0 mA	0.65 V - 3.6 V	0.65 V - 3.6 V			25			55	µA
C _i Input capacitance	Control Inputs (DIR, $\overline{\text{OE}}$): V _I = 3.3 V or GND	3.3 V	3.3 V			4.5			4.5	pF
C _{io} Data I/O capacitance	Ports A and B: $\overline{\text{OE}}$ = V _{CCA} , V _O = 1.65V DC + 1 MHz -16 dBm sine wave	3.3 V	3.3 V			5.7			5.7	pF

(1) V_{CCO} is the V_{CC} associated with the output port.

(2) All typical values are for T_A = 25°C

6.6 Switching Characteristics, $V_{CCA} = 0.7\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				0.7 V ± 0.05 V		0.8 V ± 0.04 V		0.9 V ± 0.045 V		1.2 V ± 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	172	0.5	114	0.5	82	0.5	49	ns
			−40°C to 125°C	0.5	172	0.5	114	0.5	82	0.5	49	
	B	A	−40°C to 85°C	0.5	172	0.5	153	0.5	126	0.5	88	
			−40°C to 125°C	0.5	172	0.5	153	0.5	126	0.5	88	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	192	0.5	192	0.5	192	0.5	192	ns
			−40°C to 125°C	0.5	195	0.5	195	0.5	195	0.5	195	
	\overline{OE}	B	−40°C to 85°C	0.5	156	0.5	129	0.5	118	0.5	120	
			−40°C to 125°C	0.5	157	0.5	129	0.5	120	0.5	122	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	237	0.5	237	0.5	237	0.5	237	ns
			−40°C to 125°C	0.5	237	0.5	237	0.5	237	0.5	237	
	\overline{OE}	B	−40°C to 85°C	0.5	223	0.5	145	0.5	106	0.5	74	
			−40°C to 125°C	0.5	223	0.5	145	0.5	106	0.5	74	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	46	0.5	49	0.5	61	0.5	142	ns
			−40°C to 125°C	0.5	46	0.5	49	0.5	61	0.5	142	
	B	A	−40°C to 85°C	0.5	83	0.5	82	0.5	81	0.5	81	
			−40°C to 125°C	0.5	83	0.5	82	0.5	81	0.5	81	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	192	0.5	192	0.5	192	0.5	192	ns
			−40°C to 125°C	0.5	195	0.5	195	0.5	195	0.5	195	
	\overline{OE}	B	−40°C to 85°C	0.5	69	0.5	66	0.5	67	0.5	150	
			−40°C to 125°C	0.5	70	0.5	67	0.5	67	0.5	150	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	237	0.5	237	0.5	237	0.5	237	ns
			−40°C to 125°C	0.5	237	0.5	237	0.5	237	0.5	237	
	\overline{OE}	B	−40°C to 85°C	0.5	68	0.5	69	0.5	84	0.5	552	
			−40°C to 125°C	0.5	68	0.5	69	0.5	84	0.5	552	

6.7 Switching Characteristics, $V_{CCA} = 0.8\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				0.7 V ± 0.05 V		0.8 V ± 0.04 V		0.9 V ± 0.045 V		1.2 V ± 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	153	0.5	95	0.5	62	0.5	32	ns
			−40°C to 125°C	0.5	153	0.5	95	0.5	62	0.5	32	
	B	A	−40°C to 85°C	0.5	114	0.5	95	0.5	78	0.5	52	
			−40°C to 125°C	0.5	114	0.5	95	0.5	78	0.5	52	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	101	0.5	101	0.5	101	0.5	101	ns
			−40°C to 125°C	0.5	103	0.5	103	0.5	103	0.5	103	
	\overline{OE}	B	−40°C to 85°C	0.5	141	0.5	114	0.5	104	0.5	106	
			−40°C to 125°C	0.5	142	0.5	115	0.5	106	0.5	109	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	102	0.5	102	0.5	102	0.5	102	ns
			−40°C to 125°C	0.5	102	0.5	102	0.5	102	0.5	102	
	\overline{OE}	B	−40°C to 85°C	0.5	202	0.5	124	0.5	86	0.5	52	
			−40°C to 125°C	0.5	202	0.5	124	0.5	86	0.5	52	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	26	0.5	25	0.5	25	0.5	35	ns
			−40°C to 125°C	0.5	26	0.5	25	0.5	25	0.5	35	
	B	A	−40°C to 85°C	0.5	42	0.5	41	0.5	40	0.5	40	
			−40°C to 125°C	0.5	42	0.5	41	0.5	40	0.5	40	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	101	0.5	101	0.5	101	0.5	101	ns
			−40°C to 125°C	0.5	103	0.5	103	0.5	103	0.5	103	
	\overline{OE}	B	−40°C to 85°C	0.5	55	0.5	51	0.5	49	0.5	51	
			−40°C to 125°C	0.5	57	0.5	53	0.5	50	0.5	52	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	102	0.5	102	0.5	102	0.5	102	ns
			−40°C to 125°C	0.5	102	0.5	102	0.5	102	0.5	102	
	\overline{OE}	B	−40°C to 85°C	0.5	44	0.5	43	0.5	45	0.5	58	
			−40°C to 125°C	0.5	44	0.5	43	0.5	45	0.5	58	

6.8 Switching Characteristics, $V_{CCA} = 0.9\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				0.7 V ± 0.05 V		0.8 V ± 0.04 V		0.9 V ± 0.045 V		1.2 V ± 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	127	0.5	78	0.5	52	0.5	23	ns
			−40°C to 125°C	0.5	127	0.5	78	0.5	52	0.5	23	
	B	A	−40°C to 85°C	0.5	82	0.5	63	0.5	52	0.5	39	
			−40°C to 125°C	0.5	82	0.5	63	0.5	52	0.5	39	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	125	0.5	125	0.5	125	0.5	125	ns
			−40°C to 125°C	0.5	128	0.5	128	0.5	128	0.5	128	
	\overline{OE}	B	−40°C to 85°C	0.5	131	0.5	105	0.5	96	0.5	99	
			−40°C to 125°C	0.5	133	0.5	107	0.5	98	0.5	101	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	124	0.5	124	0.5	124	0.5	124	ns
			−40°C to 125°C	0.5	128	0.5	128	0.5	128	0.5	128	
	\overline{OE}	B	−40°C to 85°C	0.5	191	0.5	113	0.5	75	0.5	41	
			−40°C to 125°C	0.5	191	0.5	113	0.5	75	0.5	41	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	17	0.5	15	0.5	14	0.5	17	ns
			−40°C to 125°C	0.5	17	0.5	15	0.5	14	0.5	17	
	B	A	−40°C to 85°C	0.5	28	0.5	24	0.5	22	0.5	22	
			−40°C to 125°C	0.5	28	0.5	24	0.5	22	0.5	22	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	125	0.5	125	0.5	125	0.5	125	ns
			−40°C to 125°C	0.5	128	0.5	128	0.5	128	0.5	128	
	\overline{OE}	B	−40°C to 85°C	0.5	47	0.5	44	0.5	40	0.5	73	
			−40°C to 125°C	0.5	50	0.5	46	0.5	42	0.5	73	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	124	0.5	124	0.5	124	0.5	124	ns
			−40°C to 125°C	0.5	128	0.5	128	0.5	128	0.5	128	
	\overline{OE}	B	−40°C to 85°C	0.5	34	0.5	32	0.5	31	0.5	35	
			−40°C to 125°C	0.5	34	0.5	32	0.5	31	0.5	35	

6.9 Switching Characteristics, $V_{CCA} = 1.2\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V_{CCB})								UNIT
				0.7 V \pm 0.05 V		0.8 V \pm 0.04 V		0.9 V \pm 0.045 V		1.2 V \pm 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	–40°C to 85°C	0.5	88	0.5	52	0.5	39	0.5	15	ns
			–40°C to 125°C	0.5	88	0.5	52	0.5	39	0.5	15	
	B	A	–40°C to 85°C	0.5	49	0.5	32	0.5	23	0.5	15	
			–40°C to 125°C	0.5	49	0.5	32	0.5	23	0.5	15	
t_{dis} Disable time	\overline{OE}	A	–40°C to 85°C	0.5	87	0.5	87	0.5	87	0.5	87	ns
			–40°C to 125°C	0.5	91	0.5	91	0.5	91	0.5	91	
	\overline{OE}	B	–40°C to 85°C	0.5	119	0.5	94	0.5	85	0.5	89	
			–40°C to 125°C	0.5	121	0.5	96	0.5	88	0.5	93	
t_{en} Enable time	\overline{OE}	A	–40°C to 85°C	0.5	34	0.5	34	0.5	34	0.5	34	ns
			–40°C to 125°C	0.5	36	0.5	36	0.5	36	0.5	36	
	\overline{OE}	B	–40°C to 85°C	0.5	168	0.5	98	0.5	61	0.5	29	
			–40°C to 125°C	0.5	168	0.5	98	0.5	61	0.5	30	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	–40°C to 85°C	0.5	10	0.5	9	0.5	7	0.5	7	ns
			–40°C to 125°C	0.5	10	0.5	9	0.5	7	0.5	8	
	B	A	–40°C to 85°C	0.5	13	0.5	11	0.5	8	0.5	7	
			–40°C to 125°C	0.5	13	0.5	11	0.5	8	0.5	7	
t_{dis} Disable time	\overline{OE}	A	–40°C to 85°C	0.5	87	0.5	87	0.5	87	0.5	87	ns
			–40°C to 125°C	0.5	91	0.5	91	0.5	91	0.5	91	
	\overline{OE}	B	–40°C to 85°C	0.5	38	0.5	35	0.5	31	0.5	29	
			–40°C to 125°C	0.5	41	0.5	38	0.5	33	0.5	31	
t_{en} Enable time	\overline{OE}	A	–40°C to 85°C	0.5	34	0.5	34	0.5	34	0.5	34	ns
			–40°C to 125°C	0.5	36	0.5	36	0.5	36	0.5	36	
	\overline{OE}	B	–40°C to 85°C	0.5	22	0.5	19	0.5	17	0.5	17	
			–40°C to 125°C	0.5	23	0.5	20	0.5	18	0.5	18	

6.10 Switching Characteristics, $V_{CCA} = 1.5\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				0.7 V ± 0.05 V		0.8 V ± 0.04 V		0.9 V ± 0.045 V		1.2 V ± 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t _{pd} Propagation delay	A	B	−40°C to 85°C	0.5	84	0.5	42	0.5	28	0.5	13	ns
			−40°C to 125°C	0.5	84	0.5	42	0.5	28	0.5	13	
	B	A	−40°C to 85°C	0.5	46	0.5	26	0.5	17	0.5	10	
			−40°C to 125°C	0.5	46	0.5	26	0.5	17	0.5	10	
t _{dis} Disable time	OE	A	−40°C to 85°C	0.5	34	0.5	34	0.5	34	0.5	34	ns
			−40°C to 125°C	0.5	37	0.5	37	0.5	37	0.5	37	
	OE	B	−40°C to 85°C	0.5	115	0.5	89	0.5	80	0.5	85	
			−40°C to 125°C	0.5	117	0.5	91	0.5	83	0.5	89	
t _{en} Enable time	OE	A	−40°C to 85°C	0.5	21	0.5	21	0.5	21	0.5	21	ns
			−40°C to 125°C	0.5	23	0.5	23	0.5	23	0.5	23	
	OE	B	−40°C to 85°C	0.5	159	0.5	90	0.5	55	0.5	24	
			−40°C to 125°C	0.5	159	0.5	90	0.5	55	0.5	25	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t _{pd} Propagation delay	A	B	−40°C to 85°C	0.5	9	0.5	7	0.5	6	0.5	5	ns
			−40°C to 125°C	0.5	9	0.5	7	0.5	6	0.5	6	
	B	A	−40°C to 85°C	0.5	9	0.5	7	0.5	6	0.5	5	
			−40°C to 125°C	0.5	9	0.5	8	0.5	6	0.5	5	
t _{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	34	0.5	34	0.5	34	0.5	34	ns
			−40°C to 125°C	0.5	37	0.5	37	0.5	37	0.5	37	
	\overline{OE}	B	−40°C to 85°C	0.5	35	0.5	31	0.5	28	0.5	25	
			−40°C to 125°C	0.5	38	0.5	34	0.5	31	0.5	27	
t _{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	21	0.5	21	0.5	21	0.5	21	ns
			−40°C to 125°C	0.5	23	0.5	23	0.5	23	0.5	23	
	\overline{OE}	B	−40°C to 85°C	0.5	17	0.5	15	0.5	12	0.5	11	
			−40°C to 125°C	0.5	18	0.5	15	0.5	13	0.5	12	

6.11 Switching Characteristics, $V_{CCA} = 1.8\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				0.7 V ± 0.05 V		0.8 V ± 0.04 V		0.9 V ± 0.045 V		1.2 V ± 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	–40°C to 85°C	0.5	82	0.5	41	0.5	24	0.5	11	ns
			–40°C to 125°C	0.5	82	0.5	41	0.5	24	0.5	11	
	B	A	–40°C to 85°C	0.5	49	0.5	25	0.5	15	0.5	9	
			–40°C to 125°C	0.5	49	0.5	25	0.5	15	0.5	9	
t_{dis} Disable time	\overline{OE}	A	–40°C to 85°C	0.5	37	0.5	37	0.5	37	0.5	37	ns
			–40°C to 125°C	0.5	40	0.5	40	0.5	40	0.5	40	
	\overline{OE}	B	–40°C to 85°C	0.5	113	0.5	87	0.5	78	0.5	83	
			–40°C to 125°C	0.5	115	0.5	89	0.5	81	0.5	87	
t_{en} Enable time	\overline{OE}	A	–40°C to 85°C	0.5	17	0.5	17	0.5	17	0.5	17	ns
			–40°C to 125°C	0.5	19	0.5	19	0.5	19	0.5	19	
	\overline{OE}	B	–40°C to 85°C	0.5	157	0.5	88	0.5	54	0.5	23	
			–40°C to 125°C	0.5	157	0.5	88	0.5	54	0.5	23	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	–40°C to 85°C	0.5	8	0.5	6	0.5	5	0.5	5	ns
			–40°C to 125°C	0.5	8	0.5	7	0.5	6	0.5	5	
	B	A	–40°C to 85°C	0.5	7	0.5	6	0.5	5	0.5	4	
			–40°C to 125°C	0.5	7	0.5	7	0.5	5	0.5	4	
t_{dis} Disable time	\overline{OE}	A	–40°C to 85°C	0.5	37	0.5	37	0.5	37	0.5	37	ns
			–40°C to 125°C	0.5	40	0.5	40	0.5	40	0.5	40	
	\overline{OE}	B	–40°C to 85°C	0.5	33	0.5	30	0.5	27	0.5	57	
			–40°C to 125°C	0.5	36	0.5	33	0.5	29	0.5	60	
t_{en} Enable time	\overline{OE}	A	–40°C to 85°C	0.5	17	0.5	17	0.5	17	0.5	17	ns
			–40°C to 125°C	0.5	19	0.5	19	0.5	19	0.5	19	
	\overline{OE}	B	–40°C to 85°C	0.5	15	0.5	13	0.5	10	0.5	9	
			–40°C to 125°C	0.5	16	0.5	14	0.5	11	0.5	10	

6.12 Switching Characteristics, $V_{CCA} = 2.5\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				0.7 V ± 0.05 V		0.8 V ± 0.04 V		0.9 V ± 0.045 V		1.2 V ± 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	81	0.5	40	0.5	22	0.5	8	ns
			−40°C to 125°C	0.5	81	0.5	40	0.5	22	0.5	8	
	B	A	−40°C to 85°C	0.5	61	0.5	25	0.5	14	0.5	7	
			−40°C to 125°C	0.5	61	0.5	25	0.5	14	0.5	7	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	25	0.5	25	0.5	25	0.5	25	ns
			−40°C to 125°C	0.5	28	0.5	28	0.5	28	0.5	28	
	\overline{OE}	B	−40°C to 85°C	0.5	111	0.5	85	0.5	76	0.5	81	
			−40°C to 125°C	0.5	113	0.5	87	0.5	78	0.5	84	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	11	0.5	11	0.5	11	0.5	11	ns
			−40°C to 125°C	0.5	12	0.5	12	0.5	12	0.5	12	
	\overline{OE}	B	−40°C to 85°C	0.5	155	0.5	86	0.5	52	0.5	21	
			−40°C to 125°C	0.5	155	0.5	86	0.5	52	0.5	21	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	–40°C to 85°C	0.5	6	0.5	5	0.5	4	0.5	4	ns
			–40°C to 125°C	0.5	6	0.5	5	0.5	5	0.5	4	
	B	A	–40°C to 85°C	0.5	6	0.5	5	0.5	4	0.5	4	
			–40°C to 125°C	0.5	6	0.5	5	0.5	5	0.5	4	
t_{dis} Disable time	\overline{OE}	A	–40°C to 85°C	0.5	25	0.5	25	0.5	25	0.5	25	ns
			–40°C to 125°C	0.5	28	0.5	28	0.5	28	0.5	28	
	\overline{OE}	B	–40°C to 85°C	0.5	31	0.5	28	0.5	25	0.5	23	
			–40°C to 125°C	0.5	34	0.5	31	0.5	28	0.5	25	
t_{en} Enable time	\overline{OE}	A	–40°C to 85°C	0.5	11	0.5	11	0.5	11	0.5	11	ns
			–40°C to 125°C	0.5	12	0.5	12	0.5	12	0.5	12	
	\overline{OE}	B	–40°C to 85°C	0.5	14	0.5	11	0.5	9	0.5	7	
			–40°C to 125°C	0.5	14	0.5	12	0.5	9	0.5	8	

6.13 Switching Characteristics, $V_{CCA} = 3.3\text{ V}$

See [Figure 1](#) and [Figure 2](#) for test circuit and loading conditions. See [Figure 3](#) and [Figure 4](#) for measurement waveforms.

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				0.7 V ± 0.05 V		0.8 V ± 0.04 V		0.9 V ± 0.045 V		1.2 V ± 0.1 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	81	0.5	40	0.5	22	0.5	7	ns
			−40°C to 125°C	0.5	81	0.5	40	0.5	22	0.5	7	
	B	A	−40°C to 85°C	0.5	142	0.5	35	0.5	17	0.5	7	
			−40°C to 125°C	0.5	142	0.5	35	0.5	17	0.5	8	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	22	0.5	22	0.5	22	0.5	22	ns
			−40°C to 125°C	0.5	24	0.5	24	0.5	24	0.5	24	
	\overline{OE}	B	−40°C to 85°C	0.5	111	0.5	84	0.5	75	0.5	80	
			−40°C to 125°C	0.5	113	0.5	86	0.5	78	0.5	83	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	9	0.5	9	0.5	9	0.5	9	ns
			−40°C to 125°C	0.5	10	0.5	10	0.5	10	0.5	10	
	\overline{OE}	B	−40°C to 85°C	0.5	154	0.5	86	0.5	51	0.5	20	
			−40°C to 125°C	0.5	154	0.5	86	0.5	51	0.5	20	

PARAMETER	FROM	TO	Test Conditions	B-Port Supply Voltage (V _{CCB})								UNIT
				1.5 V ± 0.1 V		1.8 V ± 0.15 V		2.5 V ± 0.2 V		3.3 V ± 0.3 V		
				MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
t_{pd} Propagation delay	A	B	−40°C to 85°C	0.5	5	0.5	4	0.5	4	0.5	4	ns
			−40°C to 125°C	0.5	5	0.5	4	0.5	4	0.5	4	
	B	A	−40°C to 85°C	0.5	5	0.5	5	0.5	4	0.5	4	
			−40°C to 125°C	0.5	6	0.5	5	0.5	4	0.5	4	
t_{dis} Disable time	\overline{OE}	A	−40°C to 85°C	0.5	22	0.5	22	0.5	22	0.5	22	ns
			−40°C to 125°C	0.5	24	0.5	24	0.5	24	0.5	24	
	\overline{OE}	B	−40°C to 85°C	0.5	30	0.5	27	0.5	25	0.5	23	
			−40°C to 125°C	0.5	33	0.5	30	0.5	27	0.5	25	
t_{en} Enable time	\overline{OE}	A	−40°C to 85°C	0.5	9	0.5	9	0.5	9	0.5	9	ns
			−40°C to 125°C	0.5	10	0.5	10	0.5	10	0.5	10	
	\overline{OE}	B	−40°C to 85°C	0.5	13	0.5	10	0.5	8	0.5	7	
			−40°C to 125°C	0.5	14	0.5	11	0.5	8	0.5	7	

SN74AXC8T245

SCES875 – MARCH 2018 – REVISED JULY 2018

www.ti.com
6.14 Operating Characteristics: $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_{pdA} Power dissipation capacitance per transceiver (A to B: outputs enabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	1.2		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	2		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	2.5		
C_{pdA} Power dissipation capacitance per transceiver (A to B: outputs disabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	1.1		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	2		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	2.1		
C_{pdA} Power dissipation capacitance per transceiver (B to A: outputs enabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	9.3		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	11.8		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	11.8		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	12		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	12.2		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	13		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	16.4		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	18.1		
C_{pdA} Power dissipation capacitance per transceiver (B to A: outputs disabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	2.6		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	1.2		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	1.1		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	1.2		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	1.2		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	1.3		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	1.6		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	3.9		


Operating Characteristics: $T_A = 25^\circ\text{C}$ (continued)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_{pdB} Power dissipation capacitance per transceiver (A to B: outputs enabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	9.3		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	11.7		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	11.8		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	11.9		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	12.2		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	12.9		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	16.3		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	18		
C_{pdB} Power dissipation capacitance per transceiver (A to B: outputs disabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	2.6		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	11.7		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	11.8		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	11.9		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	12.2		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	12.9		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	16.3		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	3.9		
C_{pdB} Power dissipation capacitance per transceiver (B to A: outputs enabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	1.2		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	2		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	2.5		
C_{pdB} Power dissipation capacitance per transceiver (B to A: outputs disabled)	$C_L = 0$, $R_L = \text{Open}$ $f = 1\text{ MHz}$, $t_r = t_f = 1\text{ ns}$	$V_{CCA} = V_{CCB} = 0.7\text{ V}$	1.1		pF
		$V_{CCA} = V_{CCB} = 0.8\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 0.9\text{ V}$	1.8		
		$V_{CCA} = V_{CCB} = 1.2\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.5\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 1.8\text{ V}$	1.7		
		$V_{CCA} = V_{CCB} = 2.5\text{ V}$	2		
		$V_{CCA} = V_{CCB} = 3.3\text{ V}$	2.1		

7 Parameter Measurement Information

Unless otherwise noted, all input pulses are supplied by generators having the following characteristics:

- $f = 1 \text{ MHz}$
- $Z_0 = 50 \Omega$
- $dv / dt \leq 1 \text{ ns/V}$



(1) C_L includes probe and jig capacitance.


Figure 1. Load Circuit

Parameter	V_{CCO}	R_L	C_L	S1	V_{TP}
t_{pd}	1.1 V - 3.6 V	2 k Ω	15 pF	Open	N/A
	0.65 V - 0.95 V	20 k Ω	15 pF	Open	N/A
$t_{en}^{(1)}, t_{dis}^{(1)}$	3 V - 3.6 V	2 k Ω	15 pF	2 X V_{CCO}	0.3 V
	1.65 V - 2.7 V	2 k Ω	15 pF	2 X V_{CCO}	0.15 V
	1.1 V - 1.6 V	2 k Ω	15 pF	2 X V_{CCO}	0.1 V
	0.65 V - 0.95 V	20 k Ω	15 pF	2 X V_{CCO}	0.1 V
$t_{en}^{(2)}, t_{dis}^{(2)}$	3 V - 3.6 V	2 k Ω	15 pF	GND	0.3 V
	1.65 V - 2.7 V	2 k Ω	15 pF	GND	0.15 V
	1.1 V - 1.6 V	2 k Ω	15 pF	GND	0.1 V
	0.65 V - 0.95 V	20 k Ω	15 pF	GND	0.1 V

(1) Output waveform on the conditions that input is driven to a valid Logic Low.

(2) Output waveform on the condition that input is driven to a valid Logic High.

Figure 2. Load Circuit Conditions




(1) V_{CCI} is the supply pin associated with the input port.

(2) V_{OH} and V_{OL} are typical output voltage levels with specified R_L , C_L , and S_1 .

Figure 3. Propagation Delay

Parameter Measurement Information (continued)



- (1) Output waveform on the condition that input is driven to a valid Logic Low.
- (2) Output waveform on the condition that input is driven to a valid Logic High.
- (3) V_{CCO} is the supply pin associated with the output port.
- (4) V_{OH} and V_{OL} are typical output voltage levels with specified R_L , C_L , and S_1 .


Figure 4. Enable Time And Disable Time

8 Detailed Description

8.1 Overview

The SN74AXC8T245 device is an 8-bit, dual-supply non-inverting transceiver with bidirectional voltage level translation. The I/O pins labeled with A and the control pins (DIR1, DIR2, and \overline{OE}) are supported by V_{CCA} , and the I/O pins labeled with B are supported by V_{CCB} . Both the A port and the B port are able to accept I/O voltages ranging from 0.65 V to 3.6 V.

8.2 Functional Block Diagram



8.3 Feature Description

8.3.1 Up-Translation and Down-Translation From 0.65 V to 3.6 V

Both supply pins are configured from 0.65 V to 3.6 V, which makes the device suitable for translating between any of the low voltage nodes (0.7 V, 0.8 V, 0.9 V, 1.2 V, 1.8 V, 2.5 V, and 3.3 V).

8.3.2 Multiple Direction Control Pins

Two control pins are used to configure the 8 data I/Os. I/O channels 1 through 4 are grouped together and I/O channels 5 through 8 are banked together. The benefit of this is to permit simultaneous up-translation and down-translation within one device. This eliminates the need for multiple devices, where each device can only provide up-translation or down-translation sequentially. Simultaneous up and down translation is supported when both V_{CCA} and V_{CCB} are at least 1.40 V.

8.3.3 I_{off} Supports Partial-Power-Down Mode Operation

This feature is to limit the leakage current of an I/O pin being driven to a voltage as large as 3.6 V while having its corresponding power supply rail powered down. This is represented by the I_{off} parameter in the [Electrical Characteristics](#) table.

8.4 Device Functional Modes

All control inputs are referenced to V_{CCA} and must be driven to a valid Logic High or Logic Low (that is, not floating) to assure proper device operation and to prevent excessive power consumption. [Table 1](#) summarizes the possible modes of device operation based on the configuration of the control inputs.

Table 1. Function Table⁽¹⁾

CONTROL INPUTS			Signal Direction	
\overline{OE}	DIR1	DIR2	Bits 1:4	Bits 5:8
H	X	X	Disabled (Hi-Z)	
L	L	L	B to A	
L	L	H	B to A	A to B
L	H	L	A to B	
L	H	H	A to B	B to A

(1) Input circuits of the data I/Os are always active and must be driven to a valid logic level.

9 Application and Implementation

NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

9.1 Application Information

The SN74AXC8T245 device can be used in level-translation applications for interfacing devices or systems operating at different voltage nodes. [Figure 5](#) depicts an application in which the SN74AXC8T245 device is up-translating a 0.7 V input to a 3.3 V output to interface between a system controller and a peripheral device.

9.2 Typical Application




Figure 5. Typical Application Schematic

Typical Application (continued)

9.2.1 Design Requirements

For this design example, use the parameters listed in [Table 2](#).

Table 2. Design Parameters

DESIGN PARAMETERS	EXAMPLE VALUE
Input voltage range	0.65 V to 3.6 V
Output voltage range	0.65 V to 3.6 V

9.2.2 Detailed Design Procedure

To begin the design process, determine the following:

- Input voltage range
 - Use the supply voltage of the device that is driving the SN74AXC8T245 device to determine the input voltage range. For a valid logic high the value must exceed the V_{IH} of the input port. For a valid logic low the value must be less than the V_{IL} of the input port.
- Output voltage range
 - Use the supply voltage of the device that the SN74AXC8T245 device is driving to determine the output voltage range.

9.2.3 Application Curve




Figure 6. Translation Up (0.7 V to 3.3 V) at 2.5 MHz

10 Power Supply Recommendations

Always apply a ground reference to the GND pins first. However, there are no additional requirements for power supply sequencing.

This device was designed with various power supply sequencing methods in mind to help prevent unintended triggering of downstream devices. For more information regarding the power up glitch performance of the AXC family of level translators, see the [Power Sequencing for AXC Family of Devices](#) application report.


11 Layout

11.1 Layout Guidelines

To assure reliability of the device, follow common printed-circuit board layout guidelines.

- Use bypass capacitors on power supplies.
- Use short trace lengths to avoid excessive loading.
- Place pads on the signal paths for loading capacitors or pullup resistors to help adjust rise and fall times of signals depending on the system requirements.

11.2 Layout Example



12 Device and Documentation Support

12.1 Documentation Support

12.1.1 Related Documentation

For related documentation see the following:

Texas Instruments, [Implications of Slow or Floating CMOS Inputs](#) application report

Texas Instruments, [Power Sequencing for AXC Family of Devices](#) application report

12.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

12.3 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

TI E2E™ Online Community *TI's Engineer-to-Engineer (E2E) Community*. Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

Design Support *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

12.4 Trademarks

E2E is a trademark of Texas Instruments.

All other trademarks are the property of their respective owners.

12.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

12.6 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

13 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
SN74AXC8T245PWR	ACTIVE	TSSOP	PW	24	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	AX8T245	Samples
SN74AXC8T245RHLR	ACTIVE	VQFN	RHL	24	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 125	AX8T245	Samples

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN74AXC8T245PWR	TSSOP	PW	24	2000	330.0	16.4	6.95	8.3	1.6	8.0	16.0	Q1
SN74AXC8T245RHLR	VQFN	RHL	24	3000	330.0	12.4	3.8	5.8	1.2	8.0	12.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN74AXC8T245PWR	TSSOP	PW	24	2000	367.0	367.0	38.0
SN74AXC8T245RHLR	VQFN	RHL	24	3000	367.0	367.0	35.0

PW (R-PDSO-G24)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - B. This drawing is subject to change without notice.
 - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
 - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
 - E. Falls within JEDEC MO-153

PW (R-PDSO-G24)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate design.
 - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
 - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

RHL (R-PVQFN-N24)

PLASTIC QUAD FLATPACK NO-LEAD



Bottom View

4205346-4/J 12/11

- NOTES:
- All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - This drawing is subject to change without notice.
 - QFN (Quad Flatpack No-Lead) package configuration.
 - The package thermal pad must be soldered to the board for thermal and mechanical performance.
 - See the additional figure in the Product Data Sheet for details regarding the exposed thermal pad features and dimensions.
 - JEDEC MO-241 package registration pending.

RHL (S-PVQFN-N24)


PLASTIC QUAD FLATPACK NO-LEAD

THERMAL INFORMATION

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271. This document is available at www.ti.com.

The exposed thermal pad dimensions for this package are shown in the following illustration.



Bottom View


Exposed Thermal Pad Dimensions

4206363-4/N 07/14

NOTE: All linear dimensions are in millimeters

RHL (R-PVQFN-N24)

PLASTIC QUAD FLATPACK NO-LEAD



- NOTES:
- All linear dimensions are in millimeters.
 - This drawing is subject to change without notice.
 - Publication IPC-7351 is recommended for alternate designs.
 - This package is designed to be soldered to a thermal pad on the board. Refer to Application Note, Quad Flat-Pack Packages, Texas Instruments Literature No. SLUA271, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at www.ti.com <<http://www.ti.com>>.
 - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
 - Customers should contact their board fabrication site for minimum solder mask web tolerances between signal pads.

IMPORTANT NOTICE

Texas Instruments Incorporated (TI) reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

TI's published terms of sale for semiconductor products (<http://www.ti.com/sc/docs/stdterms.htm>) apply to the sale of packaged integrated circuit products that TI has qualified and released to market. Additional terms may apply to the use or sale of other types of TI products and services.

Reproduction of significant portions of TI information in TI data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such reproduced documentation. Information of third parties may be subject to additional restrictions. Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyers and others who are developing systems that incorporate TI products (collectively, "Designers") understand and agree that Designers remain responsible for using their independent analysis, evaluation and judgment in designing their applications and that Designers have full and exclusive responsibility to assure the safety of Designers' applications and compliance of their applications (and of all TI products used in or for Designers' applications) with all applicable regulations, laws and other applicable requirements. Designer represents that, with respect to their applications, Designer has all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. Designer agrees that prior to using or distributing any applications that include TI products, Designer will thoroughly test such applications and the functionality of such TI products as used in such applications.

TI's provision of technical, application or other design advice, quality characterization, reliability data or other services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using TI Resources in any way, Designer (individually or, if Designer is acting on behalf of a company, Designer's company) agrees to use any particular TI Resource solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

Designer is authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY DESIGNER AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Unless TI has explicitly designated an individual product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949 and ISO 26262), TI is not responsible for any failure to meet such industry standard requirements.

Where TI specifically promotes products as facilitating functional safety or as compliant with industry functional safety standards, such products are intended to help enable customers to design and create their own applications that meet applicable functional safety standards and requirements. Using products in an application does not by itself establish any safety features in the application. Designers must ensure compliance with safety-related requirements and standards applicable to their applications. Designer may not use any TI products in life-critical medical equipment unless authorized officers of the parties have executed a special contract specifically governing such use. Life-critical medical equipment is medical equipment where failure of such equipment would cause serious bodily injury or death (e.g., life support, pacemakers, defibrillators, heart pumps, neurostimulators, and implantables). Such equipment includes, without limitation, all medical devices identified by the U.S. Food and Drug Administration as Class III devices and equivalent classifications outside the U.S.

TI may expressly designate certain products as completing a particular qualification (e.g., Q100, Military Grade, or Enhanced Product). Designers agree that it has the necessary expertise to select the product with the appropriate qualification designation for their applications and that proper product selection is at Designers' own risk. Designers are solely responsible for compliance with all legal and regulatory requirements in connection with such selection.

Designer will fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of Designer's non-compliance with the terms and provisions of this Notice.