


## FEATURES

- Members of the Texas Instruments Widebus™ Family
- State-of-the-Art Advanced BiCMOS Technology (ABT) Design for 3.3-V Operation and Low Static-Power Dissipation
- Support Mixed-Mode Signal Operation (5-V Input and Output Voltages With 3.3-V  $V_{CC}$ )
- Support Unregulated Battery Operation Down to 2.7 V
- Typical  $V_{OLP}$  (Output Ground Bounce)  $<0.8$  V at  $V_{CC} = 3.3$  V,  $T_A = 25^\circ\text{C}$
- $I_{off}$  and Power-Up 3-State Support Hot Insertion
- Bus Hold on Data Inputs Eliminates the Need for External Pullup/Pulldown Resistors
- Distributed  $V_{CC}$  and GND Pins Minimize High-Speed Switching Noise
- Flow-Through Architecture Optimizes PCB Layout
- Latch-Up Performance Exceeds 500 mA Per JESD 17
- ESD Protection Exceeds JESD 22
  - 2000-V Human-Body Model (A114-A)
  - 200-V Machine Model (A115-A)

SN54LVTH16374 . . . WD PACKAGE  
SN74LVTH16374 . . . DGG OR DL PACKAGE  
(TOP VIEW)



## DESCRIPTION/ORDERING INFORMATION

The 'LVTH16374 devices are 16-bit edge-triggered D-type flip-flops with 3-state outputs designed for low-voltage (3.3-V)  $V_{CC}$  operation, but with the capability to provide a TTL interface to a 5-V system environment. These devices are particularly suitable for implementing buffer registers, I/O ports, bidirectional bus drivers, and working registers.

These devices can be used as two 8-bit flip-flops or one 16-bit flip-flop. On the positive transition of the clock (CLK), the Q outputs of the flip-flop take on the logic levels set up at the data (D) inputs.

A buffered output-enable ( $\overline{OE}$ ) input can be used to place the eight outputs in either a normal logic state (high or low logic levels) or a high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance state and the increased drive provide the capability to drive bus lines without need for interface or pullup components.

$\overline{OE}$  does not affect internal operations of the flip-flop. Old data can be retained or new data can be entered while the outputs are in the high-impedance state.

Active bus-hold circuitry holds unused or undriven inputs at a valid logic state. Use of pullup or pulldown resistors with the bus-hold circuitry is not recommended.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Widebus is a trademark of Texas Instruments.

# SN54LVTH16374, SN74LVTH16374

## 3.3-V ABT 16-BIT EDGE-TRIGGERED D-TYPE FLIP-FLOPS WITH 3-STATE OUTPUTS

SCBS145R–MAY 1992–REVISED AUGUST 2007

### DESCRIPTION/ORDERING INFORMATION (CONTINUED)

When  $V_{CC}$  is between 0 and 1.5 V, the devices are in the high-impedance state during power up or power down. However, to ensure the high-impedance state above 1.5 V,  $\overline{OE}$  should be tied to  $V_{CC}$  through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

These devices are fully specified for hot-insertion applications using  $I_{off}$  and power-up 3-state. The  $I_{off}$  circuitry disables the outputs, preventing damaging current backflow through the devices when they are powered down. The power-up 3-state circuitry places the outputs in the high-impedance state during power up and power down, which prevents driver conflict.


### ORDERING INFORMATION

| $T_A$          | PACKAGE <sup>(1)(2)</sup> |              | ORDERABLE PART NUMBER                | TOP-SIDE MARKING |
|----------------|---------------------------|--------------|--------------------------------------|------------------|
| –40°C to 85°C  | FBGA – GRD                | Reel of 1000 | SN74LVTH16374GRDR                    | LL374            |
|                | FBGA – ZRD (Pb-free)      |              | SN74LVTH16374ZRDR                    |                  |
|                | SSOP – DL                 | Tube of 25   | SN74LVTH16374DL<br>74LVTH16374DLG4   | LVTH16374        |
|                |                           | Reel of 1000 | SN74LVTH16374DLR<br>74LVTH16374DLRG4 |                  |
|                |                           |              | TSSOP – DGG                          |                  |
|                | VFBGA – GQL               | Reel of 1000 | SN74LVTH16374KR                      | LL374            |
|                | VFBGA – ZQL (Pb-free)     |              | SN74LVTH16374ZQLR                    |                  |
| –55°C to 125°C | CFP – WD                  | Tube         | SNJ54LVTH16374WD                     | SNJ54LVTH16374WD |

(1) Package drawings, thermal data, and symbolization are available at [www.ti.com/packaging](http://www.ti.com/packaging).

(2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at [www.ti.com](http://www.ti.com).

**GQL OR ZQL PACKAGE  
(TOP VIEW)**




**TERMINAL ASSIGNMENTS<sup>(1)</sup>  
(56-Ball GQL/ZQL Package)**

|          | 1                 | 2   | 3               | 4               | 5   | 6    |
|----------|-------------------|-----|-----------------|-----------------|-----|------|
| <b>A</b> | 1 $\overline{OE}$ | NC  | NC              | NC              | NC  | 1CLK |
| <b>B</b> | 1Q2               | 1Q1 | GND             | GND             | 1D1 | 1D2  |
| <b>C</b> | 1Q4               | 1Q3 | V <sub>CC</sub> | V <sub>CC</sub> | 1D3 | 1D4  |
| <b>D</b> | 1Q6               | 1Q5 | GND             | GND             | 1D5 | 1D6  |
| <b>E</b> | 1Q8               | 1Q7 |                 |                 | 1D7 | 1D8  |
| <b>F</b> | 2Q1               | 2Q2 |                 |                 | 2D2 | 2D1  |
| <b>G</b> | 2Q3               | 2Q4 | GND             | GND             | 2D4 | 2D3  |
| <b>H</b> | 2Q5               | 2Q6 | V <sub>CC</sub> | V <sub>CC</sub> | 2D6 | 2D5  |
| <b>J</b> | 2Q7               | 2Q8 | GND             | GND             | 2D8 | 2D7  |
| <b>K</b> | 2 $\overline{OE}$ | NC  | NC              | NC              | NC  | 2CLK |

(1) NC – No internal connection

**GRD OR ZRD PACKAGE  
(TOP VIEW)**



**TERMINAL ASSIGNMENTS<sup>(1)</sup>  
(54-Ball GRD/ZRD Package)**

|          | 1   | 2   | 3                 | 4               | 5   | 6   |
|----------|-----|-----|-------------------|-----------------|-----|-----|
| <b>A</b> | 1Q1 | NC  | 1 $\overline{OE}$ | 1CLK            | NC  | 1D1 |
| <b>B</b> | 1Q3 | 1Q2 | NC                | NC              | 1D2 | 1D3 |
| <b>C</b> | 1Q5 | 1Q4 | V <sub>CC</sub>   | V <sub>CC</sub> | 1D4 | 1D5 |
| <b>D</b> | 1Q7 | 1Q6 | GND               | GND             | 1D6 | 1D7 |
| <b>E</b> | 2Q1 | 1Q8 | GND               | GND             | 1D8 | 2D1 |
| <b>F</b> | 2Q3 | 2Q2 | GND               | GND             | 2D2 | 2D3 |
| <b>G</b> | 2Q5 | 2Q4 | V <sub>CC</sub>   | V <sub>CC</sub> | 2D4 | 2D5 |
| <b>H</b> | 2Q7 | 2Q6 | NC                | NC              | 2D6 | 2D7 |
| <b>J</b> | 2Q8 | NC  | 2 $\overline{OE}$ | 2CLK            | NC  | 2D8 |

(1) NC – No internal connection

**FUNCTION TABLE  
(EACH FLIP-FLOP)**


| INPUTS          |        |   | OUTPUT         |
|-----------------|--------|---|----------------|
| $\overline{OE}$ | CLK    | D | Q              |
| L               | ↑      | H | H              |
| L               | ↑      | L | L              |
| L               | H or L | X | Q <sub>0</sub> |
| H               | X      | X | Z              |

# SN54LVTH16374, SN74LVTH16374

## 3.3-V ABT 16-BIT EDGE-TRIGGERED D-TYPE FLIP-FLOPS WITH 3-STATE OUTPUTS

SCBS145R–MAY 1992–REVISED AUGUST 2007

### LOGIC DIAGRAM (POSITIVE LOGIC)



Pin numbers shown are for the DGG, DL, and WD packages.

### Absolute Maximum Ratings<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|               |   | MIN             | MAX            | UNIT |
|---------------|---|-----------------|----------------|------|
| $V_{CC}$      | Supply voltage range  | -0.5            | 4.6            | V    |
| $V_I$         | Input voltage range <sup>(2)</sup>  | -0.5            | 7              | V    |
| $V_O$         | Voltage range applied to any output in the high-impedance or power-off state <sup>(2)</sup> | -0.5            | 7              | V    |
| $V_O$         | Voltage range applied to any output in the high state <sup>(2)</sup>                        | -0.5            | $V_{CC} + 0.5$ | V    |
| $I_O$         | Current into any output in the low state  | SN54LVTH16374   | 96             | mA   |
|               |   | SN74LVTH16374   | 128            |      |
| $I_O$         | Current into any output in the high state <sup>(3)</sup>                                    | SN54LVTH16374   | 48             | mA   |
|               |   | SN74LVTH16374   | 64             |      |
| $I_{IK}$      | Input clamp current   | $V_I < 0$       | -50            | mA   |
| $I_{OK}$      | Output clamp current  | $V_O < 0$       | -50            | mA   |
| $\theta_{JA}$ | Package thermal impedance <sup>(4)</sup>  | DGG package     | 70             | °C/W |
|               |   | DL package      | 63             |      |
|               |   | GQL/ZQL package | 42             |      |
|               |   | GRD/ZRD package | 36             |      |
| $T_{stg}$     | Storage temperature range   | -65             | 150            | °C   |

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output negative-voltage ratings may be exceeded if the input and output clamp-current ratings are observed.
- (3) This current flows only when the output is in the high state and  $V_O > V_{CC}$ .
- (4) The package thermal impedance is calculated in accordance with JESD 51-7.

### Recommended Operating Conditions<sup>(1)</sup>

|                     |                                    | SN54LVTH16374   |     | SN74LVTH16374 |     | UNIT |
|---------------------|------------------------------------|-----------------|-----|---------------|-----|------|
|                     |                                    | MIN             | MAX | MIN           | MAX |      |
| V <sub>CC</sub>     | Supply voltage                     | 2.7             | 3.6 | 2.7           | 3.6 | V    |
| V <sub>IH</sub>     | High-level input voltage           | 2               |     | 2             |     | V    |
| V <sub>IL</sub>     | Low-level input voltage            |                 | 0.8 |               | 0.8 | V    |
| V <sub>I</sub>      | Input voltage                      |                 | 5.5 |               | 5.5 | V    |
| I <sub>OH</sub>     | High-level output current          |                 | –24 |               | –32 | mA   |
| I <sub>OL</sub>     | Low-level output current           |                 | 48  |               | 64  | mA   |
| Δt/Δv               | Input transition rise or fall rate | Outputs enabled |     | 10            | 10  | ns/V |
| Δt/ΔV <sub>CC</sub> | Power-up ramp rate                 | 200             |     | 200           |     | μs/V |
| T <sub>A</sub>      | Operating free-air temperature     | –55             | 125 | –40           | 85  | °C   |

- (1) All unused control inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

# SN54LVTH16374, SN74LVTH16374

## 3.3-V ABT 16-BIT EDGE-TRIGGERED D-TYPE FLIP-FLOPS WITH 3-STATE OUTPUTS

SCBS145R–MAY 1992–REVISED AUGUST 2007

### Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER                      | TEST CONDITIONS   |  | SN54LVTH16374                    |                    |     | SN74LVTH16374  |                    |             | UNIT          |               |
|--------------------------------|---|--|----------------------------------|--------------------|-----|----------------|--------------------|-------------|---------------|---------------|
|                                |   |  | MIN                              | TYP <sup>(1)</sup> | MAX | MIN            | TYP <sup>(1)</sup> | MAX         |               |               |
| $V_{IK}$                       | $V_{CC} = 2.7\text{ V}$ , $I_I = -18\text{ mA}$   |  | -1.2                             |                    |     | -1.2           |                    |             | V             |               |
| $V_{OH}$                       | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$ , $I_{OH} = -100\text{ }\mu\text{A}$  |  | $V_{CC} - 0.2$                   |                    |     | $V_{CC} - 0.2$ |                    |             | V             |               |
|                                | $V_{CC} = 2.7\text{ V}$ , $I_{OH} = -8\text{ mA}$   |  | 2.4                              |                    |     | 2.4            |                    |             |               |               |
|                                | $V_{CC} = 3\text{ V}$   | $I_{OH} = -24\text{ mA}$                               | 2                                |                    |     | 2              |                    |             |               |               |
| $I_{OH} = -32\text{ mA}$       |   |  |                                  |                    |     |                |                    |             |               |               |
| $V_{OL}$                       | $V_{CC} = 2.7\text{ V}$   | $I_{OL} = 100\text{ }\mu\text{A}$                      | 0.2                              |                    |     | 0.2            |                    |             | V             |               |
|                                |   | $I_{OL} = 24\text{ mA}$                                | 0.5                              |                    |     | 0.5            |                    |             |               |               |
|                                | $V_{CC} = 3\text{ V}$   | $I_{OL} = 16\text{ mA}$                                | 0.4                              |                    |     | 0.4            |                    |             |               |               |
|                                |   | $I_{OL} = 32\text{ mA}$                                | 0.5                              |                    |     | 0.5            |                    |             |               |               |
|                                |   | $I_{OL} = 48\text{ mA}$                                | 0.55                             |                    |     | 0.55           |                    |             |               |               |
|                                |   | $I_{OL} = 64\text{ mA}$                                |                                  |                    |     |                |                    |             |               |               |
| $I_I$                          | $V_{CC} = 0\text{ or }3.6\text{ V}$ , $V_I = 5.5\text{ V}$  |  | 10                               |                    |     | 10             |                    |             | $\mu\text{A}$ |               |
|                                | Control inputs  | $V_{CC} = 3.6\text{ V}$ , $V_I = V_{CC}\text{ or GND}$ |                                  | $\pm 1$            |     |                | $\pm 1$            |             |               |               |
|                                | Data inputs   | $V_{CC} = 3.6\text{ V}$                                | $V_I = V_{CC}$                   | 1                  |     |                | 1                  |             |               |               |
| $V_I = 0$                      |   |  | -5                               |                    |     | -5             |                    |             |               |               |
| $I_{off}$                      | $V_{CC} = 0$ , $V_I\text{ or }V_O = 0\text{ to }4.5\text{ V}$   |  |                                  |                    |     | $\pm 100$      |                    |             | $\mu\text{A}$ |               |
| $I_{I(\text{hold})}$           | Data inputs   | $V_{CC} = 3\text{ V}$                                  | $V_I = 0.8\text{ V}$             | 75                 |     |                | 75                 |             |               | $\mu\text{A}$ |
|                                |   |  | $V_I = 2\text{ V}$               | -75                |     |                | -75                |             |               |               |
|                                |   | $V_{CC} = 3.6\text{ V}$ , <sup>(2)</sup>               | $V_I = 0\text{ to }3.6\text{ V}$ |                    |     |                |                    | 500<br>-750 |               |               |
| $I_{OZH}$                      | $V_{CC} = 3.6\text{ V}$ , $V_O = 3\text{ V}$  |  | 5                                |                    |     | 5              |                    |             | $\mu\text{A}$ |               |
| $I_{OZL}$                      | $V_{CC} = 3.6\text{ V}$ , $V_O = 0.5\text{ V}$  |  | -5                               |                    |     | -5             |                    |             | $\mu\text{A}$ |               |
| $I_{OZPU}$                     | $V_{CC} = 0\text{ to }1.5\text{ V}$ , $V_O = 0.5\text{ V to }3\text{ V}$ ,<br>$\overline{OE} = \text{don't care}$           |  | $\pm 100$ <sup>(3)</sup>         |                    |     | $\pm 100$      |                    |             | $\mu\text{A}$ |               |
| $I_{OZPD}$                     | $V_{CC} = 1.5\text{ V to }0$ , $V_O = 0.5\text{ V to }3\text{ V}$ ,<br>$\overline{OE} = \text{don't care}$                  |  | $\pm 100$ <sup>(3)</sup>         |                    |     | $\pm 100$      |                    |             | $\mu\text{A}$ |               |
| $I_{CC}$                       | $V_{CC} = 3.6\text{ V}$ ,<br>$I_O = 0$ ,<br>$V_I = V_{CC}\text{ or GND}$  | Outputs high   | 0.19                             |                    |     | 0.19           |                    |             | mA            |               |
|                                |   | Outputs low  | 5                                |                    |     | 5              |                    |             |               |               |
|                                |   | Outputs disabled                                       | 0.19                             |                    |     | 0.19           |                    |             |               |               |
| $\Delta I_{CC}$ <sup>(4)</sup> | $V_{CC} = 3\text{ V to }3.6\text{ V}$ ,<br>One input at $V_{CC} - 0.6\text{ V}$ ,<br>Other inputs at $V_{CC}\text{ or GND}$ |  | 0.2                              |                    |     | 0.2            |                    |             | mA            |               |
| $C_I$                          | $V_I = 3\text{ V or }0$   |  | 3                                |                    |     | 3              |                    |             | pF            |               |
| $C_O$                          | $V_O = 3\text{ V or }0$   |  | 9                                |                    |     | 9              |                    |             | pF            |               |

(1) All typical values are at  $V_{CC} = 3.3\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

(2) This is the bus-hold maximum dynamic current. It is the minimum overdrive current required to switch the input from one state to another.

(3) On products compliant to MIL-PRF-38535, this parameter is not production tested.

(4) This is the increase in supply current for each input that is at the specified TTL voltage level, rather than  $V_{CC}$  or GND.

## Timing Requirements

over recommended operating free-air temperature range (unless otherwise noted) (see [Figure 1](#))

|                    |  | SN54LVTH16374                            |     |                         |     | SN74LVTH16374                            |     |                         |     | UNIT |
|--------------------|--|--|-----|-------------------------|-----|--|-----|-------------------------|-----|------|
|                    |  | $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ |     | $V_{CC} = 2.7\text{ V}$ |     | $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ |     | $V_{CC} = 2.7\text{ V}$ |     |      |
|                    |  | MIN                                      | MAX | MIN                     | MAX | MIN                                      | MAX | MIN                     | MAX |      |
| $f_{\text{clock}}$ | Clock frequency                        | 160                                      |     | 160                     |     | 160                                      |     | 160                     |     | MHz  |
| $t_w$              | Pulse duration, CLK high or low        | 3  |     | 3                       |     | 3  |     | 3                       |     | ns   |
| $t_{\text{su}}$    | Setup time, data before CLK $\uparrow$ | 2.9                                      |     | 3.3                     |     | 1.8                                      |     | 2                       |     | ns   |
| $t_h$              | Hold time, data after CLK $\uparrow$   | 0.8                                      |     | 0.2                     |     | 0.8                                      |     | 0.1                     |     | ns   |

## Switching Characteristics

over recommended operating free-air temperature range,  $C_L = 50\text{ pF}$  (unless otherwise noted) (see [Figure 1](#))


| PARAMETER           | FROM (INPUT)           | TO (OUTPUT) | SN54LVTH16374                            |     |                         |     | SN74LVTH16374                            |                    |     |                         | UNIT |     |
|---------------------|------------------------|-------------|--|-----|-------------------------|-----|--|--------------------|-----|-------------------------|------|-----|
|                     |                        |             | $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ |     | $V_{CC} = 2.7\text{ V}$ |     | $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ |                    |     | $V_{CC} = 2.7\text{ V}$ |      |     |
|                     |                        |             | MIN                                      | MAX | MIN                     | MAX | MIN                                      | TYP <sup>(1)</sup> | MAX | MIN                     |      | MAX |
| $f_{\text{max}}$    |                        |             | 160                                      |     | 160                     |     | 160                                      |                    |     | 160                     | MHz  |     |
| $t_{\text{PLH}}$    | CLK                    | Q           | 1.4                                      | 5.6 | 6.2                     |     | 1.9                                      | 3                  | 4.5 | 5.2                     |      | ns  |
| $t_{\text{PHL}}$    |                        |             | 1.7                                      | 4.8 | 5                       |     | 2.1                                      | 2.9                | 4   | 4.2                     |      |     |
| $t_{\text{PZH}}$    | $\overline{\text{OE}}$ | Q           | 1  | 5.6 | 6.4                     |     | 1.5                                      | 2.8                | 4.5 | 5.4                     |      | ns  |
| $t_{\text{PZL}}$    |                        |             | 1.4                                      | 5.5 | 6.2                     |     | 1.5                                      | 2.8                | 4.4 | 5                       |      |     |
| $t_{\text{PHZ}}$    | $\overline{\text{OE}}$ | Q           | 1  | 6.4 | 6.9                     |     | 2.4                                      | 3.5                | 5   | 5.4                     |      | ns  |
| $t_{\text{PLZ}}$    |                        |             | 1.7                                      | 5   | 5.2                     |     | 2  | 3.2                | 4.6 | 4.8                     |      |     |
| $t_{\text{sk(LH)}}$ |                        |             |  |     |                         |     |  | 0.5                |     |                         | ns   |     |
| $t_{\text{sk(HL)}}$ |                        |             |  |     |                         |     |  | 0.5                |     |                         |      |     |

(1) All typical values are at  $V_{CC} = 3.3\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

# SN54LVTH16374, SN74LVTH16374 3.3-V ABT 16-BIT EDGE-TRIGGERED D-TYPE FLIP-FLOPS WITH 3-STATE OUTPUTS


SCBS145R—MAY 1992—REVISED AUGUST 2007

## PARAMETER MEASUREMENT INFORMATION




LOAD CIRCUIT


| TEST              | S1   |
|-------------------|------|
| $t_{PLH}/t_{PHL}$ | Open |
| $t_{PLZ}/t_{PZL}$ | 6 V  |
| $t_{PHZ}/t_{PZH}$ | GND  |




VOLTAGE WAVEFORMS  
PULSE DURATION



VOLTAGE WAVEFORMS  
SETUP AND HOLD TIMES



VOLTAGE WAVEFORMS  
PROPAGATION DELAY TIMES  
INVERTING AND NONINVERTING OUTPUTS



VOLTAGE WAVEFORMS  
ENABLE AND DISABLE TIMES  
LOW- AND HIGH-LEVEL ENABLING

- NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.  
C. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10 \text{ MHz}$ ,  $Z_O = 50 \Omega$ ,  $t_r \leq 2.5 \text{ ns}$ ,  $t_f \leq 2.5 \text{ ns}$ .  
D. The outputs are measured one at a time, with one transition per measurement.

Figure 1. Load Circuit and Voltage Waveforms

**PACKAGING INFORMATION**

| Orderable Device  | Status<br>(1) | Package Type               | Package Drawing | Pins | Package Qty | Eco Plan<br>(2)         | Lead/Ball Finish | MSL Peak Temp<br>(3) | Samples<br>(Requires Login) |
|-------------------|---------------|----------------------------|-----------------|------|-------------|-------------------------|------------------|----------------------|-----------------------------|
| 5962-9564701QXA   | ACTIVE        | CFP                        | WD              | 48   | 1           | TBD                     | Call TI          | Call TI              |                             |
| 74LVTH16374DGGRG4 | ACTIVE        | TSSOP                      | DGG             | 48   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM   |                             |
| 74LVTH16374DLRG4  | ACTIVE        | SSOP                       | DL              | 48   | 1000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM   |                             |
| SN74LVTH16374DGGR | ACTIVE        | TSSOP                      | DGG             | 48   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM   |                             |
| SN74LVTH16374DL   | ACTIVE        | SSOP                       | DL              | 48   | 25          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM   |                             |
| SN74LVTH16374DLG4 | ACTIVE        | SSOP                       | DL              | 48   | 25          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM   |                             |
| SN74LVTH16374DLR  | ACTIVE        | SSOP                       | DL              | 48   | 1000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM   |                             |
| SN74LVTH16374GQLR | OBSOLETE      | BGA<br>MICROSTAR<br>JUNIOR | GQL             | 56   |             | TBD                     | Call TI          | Call TI              |                             |
| SN74LVTH16374GRDR | OBSOLETE      | BGA<br>MICROSTAR<br>JUNIOR | GRD             | 54   |             | TBD                     | Call TI          | Call TI              |                             |
| SNJ54LVTH16374WD  | ACTIVE        | CFP                        | WD              | 48   | 1           | TBD                     | A42              | N / A for Pkg Type   |                             |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

---

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


**OTHER QUALIFIED VERSIONS OF SN54LVTH16374, SN74LVTH16374 :**

- Catalog: [SN74LVTH16374](#)
  
- Enhanced Product: [SN74LVTH16374-EP](#), [SN74LVTH16374-EP](#)
  
- Military: [SN54LVTH16374](#)


NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
  
- Enhanced Product - Supports Defense, Aerospace and Medical Applications
  
- Military - QML certified for Military and Defense Applications

## TAPE AND REEL INFORMATION




### QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



\*All dimensions are nominal

| Device            | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LVTH16374DGGR | TSSOP        | DGG             | 48   | 2000 | 330.0              | 24.4               | 8.6     | 15.8    | 1.8     | 12.0    | 24.0   | Q1            |
| SN74LVTH16374DLR  | SSOP         | DL              | 48   | 1000 | 330.0              | 32.4               | 11.35   | 16.2    | 3.1     | 16.0    | 32.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

| Device            | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LVTH16374DGGR | TSSOP        | DGG             | 48   | 2000 | 367.0       | 367.0      | 45.0        |
| SN74LVTH16374DLR  | SSOP         | DL              | 48   | 1000 | 367.0       | 367.0      | 55.0        |

WD (R-GDFP-F\*\*)

CERAMIC DUAL FLATPACK


48 LEADS SHOWN



- NOTES: A. All linear dimensions are in inches (millimeters).  
 B. This drawing is subject to change without notice.  
 C. This package can be hermetically sealed with a ceramic lid using glass frit.  
 D. Index point is provided on cap for terminal identification only  
 E. Falls within MIL STD 1835: GDFP1-F48 and JEDEC MO-146AA  
 GDFP1-F56 and JEDEC MO-146AB

GRD (R-PBGA-N54)


PLASTIC BALL GRID ARRAY



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C Falls within JEDEC MO-205 variation DD.
  - D. This package is tin-lead (SnPb). Refer to the 54 ZRD package (drawing 4204760) for lead-free.

GQL (R-PBGA-N56)

PLASTIC BALL GRID ARRAY




- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Falls within JEDEC MO-285 variation BA-2.
  - D. This package is tin-lead (SnPb). Refer to the 56 ZQL package (drawing 4204437) for lead-free.

DL (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

48 PINS SHOWN




- NOTES: A. All linear dimensions are in inches (millimeters).  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).  
 D. Falls within JEDEC MO-118

DGG (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

48 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-153

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

### Products

|                              |  |
|------------------------------|--|
| Audio                        | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers                   | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters              | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products                | <a href="http://www.dlp.com">www.dlp.com</a>   |
| DSP                          | <a href="http://dsp.ti.com">dsp.ti.com</a>   |
| Clocks and Timers            | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface                    | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                        | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt                   | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers             | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                         | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Applications Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity        | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |  |
|-------------------------------|--|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

### TI E2E Community

[e2e.ti.com](http://e2e.ti.com)