

**TRIACS**


- GLASS PASSIVATED CHIP
- FAST-ON CONNEXIONS
- IGT SPECIFIED IN FOUR QUADRANTS
- INSULATING VOLTAGE 2500 V<sub>RMS</sub>
- UL RECOGNIZED (E81734)

**DESCRIPTION**

This new design of plastic insulated power triacs offers maximum efficiency with maximum ease of mounting.

**ADVANTAGES**

- NO TAPPING REQUIRED FOR FIXING
- EXCELLENT THERMAL IMPEDANCE AND HIGH RELIABILITY CONSTRUCTION


**RD 91**  
 (Plastic)

**ABSOLUTE RATINGS** (limiting values)

| Symbol             | Parameter   | Value                               |     | Unit                   |
|--------------------|---|-------------------------------------|-----|------------------------|
| $I_{T(RMS)}$       | RMS on-state Current (360° conduction angle)  | $T_C = 75^\circ\text{C}$            | 40  | A                      |
| $I_{TSM}$          | Non Repetitive Surge Peak on-state Current<br>( $T_j$ initial = 25 °C - Half sine wave) | $t = 8.3 \text{ ms}$                | 315 | A                      |
|                    |   | $t = 10 \text{ ms}$                 | 300 |                        |
| $I^2t$             | $I^2t$ Value for Fusing   | $t = 10 \text{ ms}$                 | 450 | $\text{A}^2\text{s}$   |
| $di/dt$            | Critical Rate of Rise of on-state Current (1)   | Repetitive<br>$F = 50 \text{ Hz}$   | 10  | $\text{A}/\mu\text{s}$ |
|                    |   | Non<br>Repetitive                   | 50  |                        |
| $T_{stg}$<br>$T_i$ | Storage and Operating Junction Temperature Range  | $-40 \text{ to } 125^\circ\text{C}$ |     | $^\circ\text{C}$       |
|                    |   | $-40 \text{ to } 125^\circ\text{C}$ |     | $^\circ\text{C}$       |

| Symbol    | Parameter                             | BTA 40- |      |      |      |      | Unit |
|-----------|---------------------------------------|---------|------|------|------|------|------|
|           |                                       | 200B    | 400B | 600B | 700B | 800B |      |
| $V_{DRM}$ | Repetitive Peak off-state Voltage (2) | 200     | 400  | 600  | 700  | 800  | V    |

 (1)  $I_G = 1 \text{ A}$     $di/dt = 1 \text{ A}/\mu\text{s}$ 

 (2)  $T_j = 125^\circ\text{C}$ .

**THERMAL RESISTANCES**

| Symbol                    | Parameter   | Value |  | Unit                      |
|---------------------------|---|-------|--|---------------------------|
| $R_{th (c-h)}$            | Contact (case-heatsink) with Grease                                 | 0.15  |  | $^\circ\text{C}/\text{W}$ |
| $R_{th (j-c)} \text{ DC}$ | Junction to Case for DC   | 1.2   |  | $^\circ\text{C}/\text{W}$ |
| $R_{th (j-c)} \text{ AC}$ | Junction to Case for 360 ° Conduction Angle ( $F = 50 \text{ Hz}$ ) | 0.9   |  | $^\circ\text{C}/\text{W}$ |

## GATE CHARACTERISTICS (maximum values)


 $P_{GM} = 40 \text{ W}$  ( $t_p = 10 \mu\text{s}$ ) $P_G(\text{AV}) = 1 \text{ W}$  $I_{GM} = 10 \text{ A}$  ( $t_p = 10 \mu\text{s}$ ) $V_{GM} = 16 \text{ V}$  ( $t_p = 10 \mu\text{s}$ )

## ELECTRICAL CHARACTERISTICS

| Symbol        | Test Conditions                   |                         |                                      | Quadrants   | Min. | Typ. | Max. | Unit             |
|---------------|-----------------------------------|-------------------------|--------------------------------------|-------------|------|------|------|------------------|
| $I_{GT}$      | $T_j = 25^\circ\text{C}$          | $V_D = 12 \text{ V}$    | $R_L = 33 \Omega$                    | I-II-III    | 1    |      | 50   | mA               |
|               | Pulse Duration > 20 $\mu\text{s}$ |                         |                                      | IV          | 1    |      | 100  |                  |
| $V_{GT}$      | $T_j = 25^\circ\text{C}$          | $V_D = 12 \text{ V}$    | $R_L = 33 \Omega$                    | I-II-III-IV |      |      | 1.5  | V                |
| $V_{GD}$      | $T_j = 125^\circ\text{C}$         | $V_D = V_{DRM}$         | $R_L = 3.3 \text{ k}\Omega$          | I-II-III-IV | 0.2  |      |      | V                |
| $I_H^*$       | $T_j = 25^\circ\text{C}$          | $I_T = 500 \text{ mA}$  | Gate Open                            |             |      | 30   | 80   | mA               |
| $I_L$         | $T_j = 25^\circ\text{C}$          | $V_D = 12 \text{ V}$    | $I_G = 200 \text{ mA}$               | I-II-III-IV |      |      | 100  | mA               |
| $V_{TM}^*$    | $T_j = 25^\circ\text{C}$          | $I_{TM} = 60 \text{ A}$ | $t_p = 10 \text{ ms}$                |             |      |      | 1.8  | V                |
| $I_{DRM}^*$   | $T_j = 125^\circ\text{C}$         | $V_{DRM}$ Specified     |                                      |             |      | 1.5  | 6    | mA               |
| $dv/dt^*$     | $T_j = 125^\circ\text{C}$         | Gate Open               |                                      |             | 250  |      |      | V/ $\mu\text{s}$ |
| $(dv/dt)_c^*$ | $T_c = 75^\circ\text{C}$          | $V_D = V_{DRM}$         | $I_T = 60 \text{ A}$                 |             | 5    |      |      | V/ $\mu\text{s}$ |
| $t_{gt}$      | $T_j = 25^\circ\text{C}$          | $V_D = V_{DRM}$         | $I_T = 60 \text{ A}$                 | I-II-III-IV |      | 2.5  |      | $\mu\text{s}$    |
|               | $I_G = 1 \text{ A}$               |                         | $di_G/dt = 10 \text{ A}/\mu\text{s}$ |             |      |      |      |                  |

\* For either polarity of electrode A<sub>2</sub> voltage with reference to electrode A<sub>1</sub>.

## PACKAGE MECHANICAL DATA : RD 91 Plastic

Tnac 1 2 3 = G A<sub>1</sub> A<sub>2</sub>

Cooling method : by conduction (method C)

Marking : type number

Weight : 15 g




Fig.1 - Maximum mean power dissipation versus RMS on-state current ( $f = 60$  Hz).




Fig.2 - Correlation between maximum mean power dissipation and maximum allowable temperatures ( $T_{amb}$  and  $T_{case}$ ) for different thermal resistances heatsink + contact.




Fig.3 - RMS on-state current versus case temperature.




Fig.4 - Thermal transient impedance junction to case versus pulse duration.




Fig.5 - Relative variation of gate trigger current and holding current versus junction temperature.




Fig.6 - Non repetitive surge peak on-state current versus number of cycles.




Fig.7 - Non repetitive surge peak on-state current for a sinusoidal pulse with width :  $t \leq 10$  ms, and corresponding value of  $I^2t$ .




Fig.8 - On-state characteristics (maximum values).