

# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.

TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960

## Triacs



### Silicon Bidirectional Triode Thyristors

...designed primarily for industrial and military applications for the control of ac loads in applications such as power supplies, heating controls, motor controls, welding equipment and power switching systems; or wherever full-wave, silicon gate controlled solid-state devices are needed.

- Glass Passivated Junctions and Center Gate Fire
- Press Fit Stud — T6400
- Stud — T6410
- Isolated Stud — T6420
- Gate Triggering Guaranteed in All 4 Quadrants

**T6400  
T6410  
T6420  
Series**

**TRIACS  
40 AMPERES RMS  
200 thru 800 VOLTS**



#### MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage, Note 1 ( $T_J = -65$ to $+110^\circ\text{C}$ ) Gate Open T6400B, T6410B, T6420B T6400D, T6410D, T6420D T6400M, T6410M, T6420M T6400N, T6410N, T6420N	$V_{DRM}$		Volts
		200	
		400	
		600	
		800	
On-State Current RMS $T_C$ (Pressfit) = $70^\circ\text{C}$ (Conduction Angle = $360^\circ$ ) $T_C$ (Stud) = $85^\circ\text{C}$	$I_{T(\text{RMS})}$	40	Amps
Peak Surge Current (Non-Repetitive) (One Full Cycle, 60 Hz)	$I_{TSM}$	300	Amps
Circuit Fusing ( $T_J = -65$ to $+110^\circ\text{C}$ , $t = 1.25$ to 10 ms)	$I^2_t$	450	$\text{A}^2\text{s}$
Peak Gate Power (Pulse Width = $1 \mu\text{s}$ )	$P_{GM}$	40	Watts
Average Gate Power	$P_{G(AV)}$	0.75	Watt
Peak Gate Current (Pulse Width = $1 \mu\text{s}$ )	$I_{GTM}$	12	Amps
Operating Temperature Range	$T_C$	-65 to +110	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	-65 to +150	$^\circ\text{C}$
Stud Torque	—	30	in. lb.

#### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case Pressfit Stud Isolated Stud	$R_{\theta JC}$	0.8 0.9 1	$^\circ\text{C/W}$

Note 1. Ratings apply for open gate conditions. Thyristor devices shall not be tested with a constant current source for blocking capability such that the voltage applied exceeds the rated blocking voltage.

NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.



## T8400 • T8410 • T8420 Series

### ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
Peak Forward or Reverse Blocking Current (Rated $V_{DRM}$ or $V_{RRM}$ , gate open) $T_J = 25^\circ\text{C}$ $T_J = 110^\circ\text{C}$	$I_{DRM}, I_{RRM}$	—	—	10 4	$\mu\text{A}$ $\text{mA}$
Maximum On-State Voltage (Either Direction) ( $I_T = 100 \text{ A Peak}$ )	$V_{TM}$	—	1.5	2	Volts
Gate Trigger Current (Continuous dc), Note 1 ( $V_D = 12 \text{ Vdc}, R_L = 30 \text{ Ohms}$ $V_{MT2(+)}, V_G(+)$ $V_{MT2(+)}, V_G(-)$ $V_{MT2(-)}, V_G(-)$ $V_{MT2(-)}, V_G(+)$ $V_{MT2(+)}, V_G(+)$ , $V_{MT2(-)}, V_G(-)$ , $T_C = -65^\circ\text{C}$ $V_{MT2(+)}, V_G(-), V_{MT2(-)}, V_G(+), T_C = -65^\circ\text{C}$ )	$I_{GT}$	—	15 30 20 40 —	50 80 50 80 125 240	$\text{mA}$
Gate Trigger Voltage (Continuous dc) ( $V_D = 12 \text{ Vdc}, R_L = 30 \text{ Ohms}, T_C = 25^\circ\text{C}$ $T_C = -65^\circ\text{C}$ ( $V_D = \text{Rated } V_{DRM}, R_L = 125 \text{ Ohms}, T_C = 110^\circ\text{C}$ )	$V_{GT}$	— 0.2	1.35 —	2.5 3.4	Volts
Holding Current (Either Direction) ( $V_D = 12 \text{ Vdc, Gate Open}$ ) (Initiating Current = 500 mA)	$I_{HO}$	— —	25 —	60 100	$\text{mA}$
Gate Controlled Turn-On Time (Rated $V_{DRM}, I_T = 60 \text{ A}, I_{GT} = 200 \text{ mA, Rise Time} = 0.1 \mu\text{s}$ )	$t_{gt}$	—	1.7	3	$\mu\text{s}$
Critical Rate of Rise of Commutation Voltage, On-State Conditions ( $dV/dt = 22 \text{ A/msec, Gate Unenergized, } V_D = \text{Rated } V_{DRM}$ , $I_T(\text{RMS}) = 40 \text{ A, } T_C (\text{Pressfit}) = 70^\circ\text{C}$ , $T_C (\text{Stud}) = 65^\circ\text{C}$ )	$dv/dt(c)$	—	5	—	$\text{V}/\mu\text{s}$

Note 1. All voltage polarities referenced to main terminal 1.

FIGURE 1 – ON-STATE POWER DISSIPATION




FIGURE 2 – RMS CURRENT DERATING

