

2N3654, 2N3655, 2N3656, 2N3657, 2N3658, S7412M


35-A Silicon Controlled Rectifiers

For Inverter Applications

Features:

- Fast turn-off time — 10 μ s max.
- High di/dt and dv/dt capability
- Low thermal resistance

TERMINAL DESIGNATIONS



JEDEC TO-208AA

The 2N3654 to 2N3658 have forward and reverse off-state voltage ratings of 50, 100, 200, 300, and 400 volts, respectively. Type S7412M has a forward and reverse off-state voltage rating of 600 volts.

These SCR's employ a hermetic JEDEC TO-208AA package.

MAXIMUM RATINGS, Absolute-Maximum Values:

	2N3654	2N3655	2N3656	2N3657	2N3658	S7412M	
*V _{RSOM} †	75	150	300	400	500	700	V
V _{OSOM} †	75	150	300	400	500	700	V
*V _{RRM} †	50	100	200	300	400	600	V
V _{ORM} †	50	100	200	300	400	600	V
I _{TRMS} (T _C = 40°C, $\theta = 180^\circ$)				35			A
I _{TRAV} (T _C = 40°C, $\theta = 180^\circ$)				25			A
*I _{TM} : For one full cycle of applied principal voltage 60-Hz (Rectangular wave-pw = 5 ms, t _r = 50 μ s), T _C = 40°C				180			A
di/dt: V _O = V _{ORM} , I _{GT} = 200 mA, t _r = 0.1 μ s (See Fig. 15)				400			A/ μ s
z _t : T _J = -65 to 120°C, t = 1 to 8.3 ms				165			A2s
*P _{OM} : Peak (forward or reverse) for 10 μ s maximum, See Fig. 7)				40			W
*P _{AVG} : Averaging time = 10 ms maximum				1			W
*T _{stg} *				-65 to 150			°C
*T _C *				-65 to 120			°C
T _r : During soldering for 10 s maximum (terminal and case)				225			°C
r _s : Recommended				35			in-lbf
Maximum (DO NOT EXCEED)				0.4			kgf-m
				50			in-lbf
				0.57			kgf-m

* In accordance with JEDEC registration data format (JS-14, RDF-1) filed for the JEDEC (2N series) types.
 † These values do not apply if there is a positive gate signal. Gate must be open or negatively biased.
 ■ Any product of gate current and gate voltage which results in a gate power less than the maximum is permitted.
 • For temperature measurement reference point, see Dimensional Outline.



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

2N3654, 2N3655, 2N3656, 2N3657, 2N3658, S7412M

ELECTRICAL CHARACTERISTICS

At Maximum Ratings Unless Otherwise Specified and at Indicated Case Temperature (T_C)

CHARACTERISTIC	LIMITS			UNITS
	FOR ALL TYPES Except as Specified			
	MIN.	TYP.	MAX.	
I_{DOM} or I_{ROM} : $V_D = V_{DROM}$ or $V_R = V_{RROM}$, $T_C = 120^\circ\text{C}$ 2N3654, 2N3655, 2N3656, S7412M 2N3657 2N3658	-	2	6*	mA
	-	2	5.5*	
	-	2	4*	
	-	2	4*	
v_T : $i_T = 25\text{ A (peak)}$, $T_C = 25^\circ\text{C}$	-	1.5	2.05*	V
i_{HO} : $T_C = 25^\circ\text{C}$ $T_C = -65^\circ\text{C}$	-	75	150	mA
	-	150	350*	
dv/dt : $V_D = V_{DROM}$, exponential voltage rise, $T_C = 120^\circ\text{C}$ (See Fig. 16)	200	-	-	V/ μs
I_{GT} : $V_D = 6\text{ V (dc)}$, $R_L = 4\ \Omega$, $T_C = 25^\circ\text{C}$ $V_D = 6\text{ V (dc)}$, $R_L = 2\ \Omega$, $T_C = -65^\circ\text{C}$	-	80	180	mA
	-	150	500*	
V_{GT} : $V_D = 6\text{ V (dc)}$, $R_L = 4\ \Omega$, $T_C = 25^\circ\text{C}$ $V_D = 6\text{ V (dc)}$, $R_L = 200\ \Omega$, $T_C = 120^\circ\text{C}$ $V_D = 6\text{ V (dc)}$, $R_L = 2\ \Omega$, $T_C = -65^\circ\text{C}$	-	1.5	3	V
	0.25	-	-	
	-	2	4.5*	
t_q : Rectangular Pulse $V_{DX} = V_{DROM}$, $i_T = 10\text{ A}$, pulse duration = 50 μs , $dv/dt = 200\text{ V}/\mu\text{s}$, $-di/dt = 5\text{ A}/\mu\text{s}$, $I_{GT} = 200\text{ mA}$ at turn-on, $V_{RX} = 15\text{ V}$ minimum, $V_{GK} = 0\text{ V}$ at turn-off, $T_C = 120^\circ\text{C}$ (See Figs. 17 & 18) Sinusoidal Pulse $V_{DX} = V_{DROM}$, $i_T = 100\text{ A}$, pulse duration = 2 μs , $dv/dt = 200\text{ V}/\mu\text{s}$, $V_{RX} = 30\text{ V}$ minimum, $V_{GK} = 0$ at turn-off, $T_C = 115^\circ\text{C}$ (See Figs. 19 & 20)	-	-	10	μs
	-	-	10	
$R_{\theta JC}$	-	0.85	1.7*	$^\circ\text{C}/\text{W}$

* In accordance with JEDEC registration data format (JS-14, RDF-1) filed for the JEDEC (2N series) types.