

V_{DRM}	=	2200 V
I_{TAVM}	=	862 A
I_{TRMS}	=	1354 A
I_{TSM}	=	12×10^3 A
$V_{(T0)}$	=	1 V
r_T	=	0.404 mΩ

Phase Control Thyristor

5STP 09D2201

Doc. No. 5SYA1059-01 March 03

- Low on-state and switching losses
- Designed for traction, energy and industrial applications
- Optimum power handling capability

Blocking

Maximum rated values ¹⁾

Symbol	Conditions	5STP 09D2201	5STP 09D2001	5STP 09D1801
V_{DRM}, V_{RRM}	$f = 50$ Hz, $t_p = 10$ ms	2200 V	2000 V	1800 V
dV/dt_{crit}	Exp. to $0.67 \times V_{DRM}$, $T_{vj} = 125^\circ\text{C}$		1000 V/μs	

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Forward leakage current	I_{DRM}	$V_{DRM}, T_{vj} = 125^\circ\text{C}$			70	mA
Reverse leakage current	I_{RRM}	$V_{RRM}, T_{vj} = 125^\circ\text{C}$			70	mA

Mechanical data

Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Mounting force	F_M		8	10	12	kN
Acceleration	a	Device unclamped			50	m/s^2
Acceleration	a	Device clamped			100	m/s^2

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Weight	m			0.26		kg
Surface creepage distance	D_S		25			mm
Air strike distance	D_a		14			mm

1) Maximum rated values indicate limits beyond which damage to the device may occur

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.



On-state*Maximum rated values¹⁾*

Parameter	Symbol	Conditions	min	typ	max	Unit
Average on-state current	$I_{T(AV)M}$	Half sine wave, $T_c = 70^\circ\text{C}$			862	A
RMS on-state current	$I_{T(RMS)}$				1354	A
Peak non-repetitive surge current	I_{TSM}	$t_p = 10 \text{ ms}, T_{vj} = 125^\circ\text{C}, V_D = V_R = 0 \text{ V}$			12×10^3	A
Limiting load integral	I^2t				720×10^3	A^2s
Peak non-repetitive surge current	I_{TSM}	$t_p = 8.3 \text{ ms}, T_{vj} = 125^\circ\text{C}, V_D = V_R = 0 \text{ V}$			12.8×10^3	A
Limiting load integral	I^2t				680×10^3	A^2s

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
On-state voltage	V_T	$I_T = 1500 \text{ A}, T_{vj} = 125^\circ\text{C}$			1.6	V
Threshold voltage	$V_{(T0)}$	$I_T = 1000 \text{ A} - 3500 \text{ A}, T_{vj} = 125^\circ\text{C}$			1	V
Slope resistance	r_T				0.404	$\text{m}\Omega$
Holding current	I_H	$T_{vj} = 25^\circ\text{C}$		170		mA
		$T_{vj} = 125^\circ\text{C}$		90		mA
Latching current	I_L	$T_{vj} = 25^\circ\text{C}$		450		mA
		$T_{vj} = 125^\circ\text{C}$		350		mA

Switching*Maximum rated values¹⁾*

Parameter	Symbol	Conditions	min	typ	max	Unit
Critical rate of rise of on-state current	di/dt_{crit}	$T_{vj} = 125^\circ\text{C}, I_T = I_{T(AV)}, f = 50 \text{ Hz}$			200	$\text{A}/\mu\text{s}$
Critical rate of rise of on-state current	di/dt_{crit}	$V_D \leq 0.67 V_{DRM}, I_{FG} = 2 \text{ A}, t_r = 0.3 \mu\text{s}$			1000	$\text{A}/\mu\text{s}$
Circuit-commutated turn-off time	t_q	$T_{vj} = 125^\circ\text{C}, I_{TRM} = 1500 \text{ A}, V_R = 200 \text{ V}, di_T/dt = -12.5 \text{ A}/\mu\text{s}, V_D \leq 0.67 \cdot V_{DRM}, dv_D/dt = 50 \text{ V}/\mu\text{s},$		200		μs

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Recovery charge	Q_{rr}	$T_{vj} = 125^\circ\text{C}, I_{TRM} = 1500 \text{ A}, V_R = 200 \text{ V}, di_T/dt = -12.5 \text{ A}/\mu\text{s}$		1600		μAs
Gate turn-on delay time	t_{gd}	$V_D = 0.4 \cdot V_{DRM}, I_{FG} = 2 \text{ A}, t_r = 0.3 \mu\text{s}, T_{vj} = 25^\circ\text{C}$			2	μs

Triggering

Maximum rated values¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Peak forward gate voltage	V _{FGM}				12	V
Peak forward gate current	I _{FGM}				10	A
Peak reverse gate voltage	V _{RGM}				10	V
Mean forward gate power	P _{G(AV)}				3	W

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Gate-trigger voltage	V _{GT}	T _{vj} = -40 °C T _{vj} = 25 °C T _{vj} = 125 °C		0.25	4 3 2	V
Gate-trigger current	I _{GT}	T _{vj} = -40 °C T _{vj} = 25 °C T _{vj} = 125 °C		10	500 250 150	mA

Thermal

Maximum rated values¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Operating junction temperature range	T _{vj}		-40		125	°C
Storage temperature range	T _{stg}		-40		125	°C

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Thermal resistance junction to case	R _{th(j-c)}	Double-side cooled			32	K/kW
	R _{th(j-c)A}	Anode-side cooled			52	K/kW
	R _{th(j-c)C}	Cathode-side cooled			83	K/kW
Thermal resistance case to heatsink	R _{th(c-h)}	Double-side cooled			7.5	K/kW
	R _{th(c-h)}	Single-side cooled			15	K/kW

Analytical function for transient thermal impedance:

$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i (1 - e^{-t/\tau_i})$$

i	1	2	3	4
R _i (K/kW)	13.070	8.030	8.200	2.700
τ _i (s)	0.4857	0.2162	0.0762	0.0043






Fig. 1 Transient thermal impedance junction-to case.

**Fig. 2** Max. on-state voltage characteristics**Fig. 3** Surge forward current vs. pulse length. Half sine wave, single pulse, $V_R = 0$ V




Fig. 4 Forward power loss vs. average forward current, sine waveform, $f = 50$ Hz, $T = 1/f$




Fig. 5 Forward power loss vs. average forward current, square waveform, $f = 50$ Hz, $T = 1/f$




Fig. 6 Max. case temperature vs. average forward current, sine waveform, $f = 50$ Hz, $T = 1/f$




Fig. 7 Max. case temperature vs. average forward current, square waveform, $f = 50$ Hz, $T = 1/f$




Fig. 8 Device Outline Drawing.

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.



ABB Switzerland Ltd
Semiconductors
Fabrikstrasse 3
CH-5600 Lenzburg, Switzerland

Doc. No. 5SYA1059-01 March 03

Telephone +41 (0)58 586 1419
Fax +41 (0)58 586 1306
Email abbsem@ch.abb.com
Internet www.abb.com/semiconductors