

V_{DSM}	=	1400 V
I_{TAVM}	=	1960 A
I_{TRMS}	=	3080 A
I_{TSM}	=	25000 A
V_{T0}	=	0.75 V
r_T	=	0.157 m Ω

Phase Control Thyristor

5STP 21F1400

Doc. No. 5SYA1023-04 Jan. 02

- Patented free-floating silicon technology
- Low on-state and switching losses
- Designed for traction, energy and industrial applications
- Optimum power handling capability

Blocking

Maximum rated values ¹⁾

Symbol	Conditions	5STP 21F1400	5STP 21F1200	5STP 21F0800
V_{DRM}, V_{RRM}	f = 50 Hz, $t_p = 10$ ms	1400 V	1200 V	800 V
V_{RSM}	$t_p = 5$ ms, single pulse	1600 V	1400 V	1000 V
dV/dt_{crit}	Exp. to $0.67 \times V_{DRM}, T_{vj} = 125^\circ\text{C}$	200 V/ μs		

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Forward leakage current	I_{DRM}	$V_{DRM}, T_{vj} = 125^\circ\text{C}$			200	mA
Reverse leakage current	I_{RRM}	$V_{RRM}, T_{vj} = 125^\circ\text{C}$			200	mA

Mechanical data

Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Mounting force	F_M		14	22	24	kN
Acceleration	a	Device unclamped			50	m/s ²
Acceleration	a	Device clamped			100	m/s ²

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Weight	m			0.6		kg
Surface creepage distance	D_s		25			mm
Air strike distance	D_a		14			mm

1) Maximum rated values are those values beyond which damage to the device may occur

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.



On-state

Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Average on-state current	I_{TAVM}	Half sine wave, $T_c = 70^\circ\text{C}$			1960	A
RMS on-state current	I_{TRMS}				3080	A
Peak non-repetitive surge current	I_{TSM}	$t_p = 10\text{ ms}$, $T_{vj} = 125^\circ\text{C}$, $V_D = V_R = 0\text{ V}$			25000	A
Limiting load integral	I^2t				3125	kA^2s
Peak non-repetitive surge current	I_{TSM}	$t_p = 8.3\text{ ms}$, $T_{vj} = 125^\circ\text{C}$, $V_D = V_R = 0\text{ V}$			26000	A
Limiting load integral	I^2t				2805	kA^2s

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
On-state voltage	V_T	$I_T = 3000\text{ A}$, $T_{vj} = 125^\circ\text{C}$			1.22	V
Threshold voltage	V_{T0}	$I_T = 1000\text{ A} - 3000\text{ A}$, $T_{vj} = 125^\circ\text{C}$			0.75	V
Slope resistance	r_T				0.157	$\text{m}\Omega$
Holding current	I_H	$T_{vj} = 25^\circ\text{C}$			70	mA
		$T_{vj} = 125^\circ\text{C}$			60	mA
Latching current	I_L	$T_{vj} = 25^\circ\text{C}$			350	mA
		$T_{vj} = 125^\circ\text{C}$			120	mA

Switching

Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Critical rate of rise of on-state current	di/dt_{crit}	$T_{vj} = 125^\circ\text{C}$, $I_{TRM} = 2000\text{ A}$, $V_D \leq 0.67 V_{DRM}$, $I_{FG} = 2\text{ A}$, $t_r = 0.5\ \mu\text{s}$			200	$\text{A}/\mu\text{s}$
Critical rate of rise of on-state current	di/dt_{crit}		Cont. $f = 50\text{ Hz}$			1000
Circuit-commutated turn-off time	t_q	$T_{vj} = 125^\circ\text{C}$, $I_{TRM} = 2000\text{ A}$, $V_R = 200\text{ V}$, $di_T/dt = -20\text{ A}/\mu\text{s}$, $V_D \leq 0.67 \cdot V_{DRM}$, $dV_D/dt = 20\text{ V}/\mu\text{s}$,	400			μs

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Recovery charge	Q_{rr}	$T_{vj} = 125^\circ\text{C}$, $I_{TRM} = 2000\text{ A}$, $V_R = 200\text{ V}$, $di_T/dt = -20\text{ A}/\mu\text{s}$	1800		3000	μAs
Delay time	t_d	$V_D = 0.4 \cdot V_{DRM}$, $I_{FG} = 2\text{ A}$, $t_r = 0.5\ \mu\text{s}$			3	μs

Triggering

Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Peak forward gate voltage	V_{FGM}				12	V
Peak forward gate current	I_{FGM}				10	A
Peak reverse gate voltage	V_{RGM}				10	V
Gate power loss	P_G	For DC gate current			3	W
Average gate power loss	P_{GAV}		see Fig. 9			

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Gate trigger voltage	V_{GT}	$T_{vj} = 25^\circ\text{C}$			2.6	V
Gate trigger current	I_{GT}	$T_{vj} = 25^\circ\text{C}$			400	mA
Gate non-trigger voltage	V_{GD}	$V_D = 0.4 \times V_{DRM}, T_{vjmax} = 125^\circ\text{C}$	0.3			V
Gate non-trigger current	I_{GD}	$V_D = 0.4 \times V_{DRM}, T_{vjmax} = 125^\circ\text{C}$	10			mA

Thermal

Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Operating junction temperature range	T_{vj}				125	$^\circ\text{C}$
Storage temperature range	T_{stg}		-40		140	$^\circ\text{C}$

Characteristic values

Parameter	Symbol	Conditions	min	typ	max	Unit
Thermal resistance junction to case	$R_{th(j-c)}$	Double-side cooled			17	K/kW
	$R_{th(j-c)A}$	Anode-side cooled			33	K/kW
	$R_{th(j-c)C}$	Cathode-side cooled			35	K/kW
Thermal resistance case to heatsink	$R_{th(c-h)}$	Double-side cooled			4	K/kW
	$R_{th(c-h)}$	Single-side cooled			8	K/kW

Analytical function for transient thermal impedance:

$$Z_{thJC}(t) = \sum_{i=1}^n R_i(1 - e^{-t/\tau_i})$$

i	1	2	3	4
R_i (K/kW)	10.35	3.76	2.29	0.67
τ_i (s)	0.3723	0.0525	0.0057	0.0023




Fig. 1 Transient thermal impedance junction-to case.




Fig. 2 On-state characteristics.




Fig. 3 On-state characteristics.
 $T_j=125^\circ\text{C}$, 10ms half sine




Fig. 4 On-state power dissipation vs. mean on-state current. Turn - on losses excluded.




Fig. 5 Max. permissible case temperature vs. mean on-state current.




Fig. 6 Surge on-state current vs. pulse length. Half-sine wave.




Fig. 7 Surge on-state current vs. number of pulses. Half-sine wave, 10 ms, 50Hz.




Fig. 8 Recommended gate current waveform.




Fig. 9 Max. peak gate power loss.




Fig. 10 Recovery charge vs. decay rate of on-state current.




Fig. 11 Peak reverse recovery current vs. decay rate of on-state current.




Fig. 12 Device Outline Drawing.

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.

ABB

ABB Switzerland Ltd
Semiconductors
Fabrikstrasse 3
CH-5600 Lenzburg, Switzerland

Telephone +41 (0)58 586 1419
Fax +41 (0)58 586 1306
Email abbsem@ch.abb.com
Internet www.abbsem.com

Doc. No. 5SYA1023-04 Jan. 02