


THYRISTORS

- GLASS PASSIVATED CHIP
- POSSIBILITY OF MOUNTING ON PRINTED CIRCUIT
- AVAILABLE IN NON-INSULATED VERSION -> TYN SERIES OR IN INSULATED VERSION -> TXN SERIES (INSULATING VOLTAGE 2500 V_{RMS})
- UL RECOGNIZED FOR TXN SERIES (E81734)


 TO 220 AB
 (Plastic)

DESCRIPTION

SCR's designed for motor control, heating controls, power supplies...

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter	Value		Unit
I _{T(RMS)}	RMS on-state Current (1)	T _c = 80 °C	12	A
I _{T(AV)}	Mean on-state Current (1)	T _c = 80 °C	8	A
I _{TSM}	Non Repetitive Surge Peak on-state Current (T _j initial = 25 °C) (2)	t = 8.3 ms	125	A
		t = 10 ms	120	
I ² t	I ² t Value for Fusing	t = 10 ms	72	A ² s
di/dt	Critical Rate of Rise of on-state Current (3)		100	A/μs
T _{stg} T _j	Storage and Operating Junction Temperature Range	– 40 to 125		°C
		– 40 to 125		°C

Symbol	Parameter	TXN/TYN							Unit
		0512	112	212	412	612	812	1012	
V _{DRM} V _{RRM}	Repetitive Peak off-state Voltage (4)	50	100	200	400	600	800	1000	V

(1) Single phase circuit, 180° conduction angle.

(2) Half sine wave.

(3) I_g = 150 mA di_g/dt = 1 A/μs.

(4) T_j = 125 °C.

THERMAL RESISTANCES

Symbol	Parameter	Value		Unit
R _{th} (j-c)	Junction-case for D.C.	3.8		°C/W
R _{th} (j-a)	Junction-ambient	60		°C/W

GATE CHARACTERISTICS (maximum values) $P_{GM} = 20 \text{ W}$ ($t_p = 20 \mu\text{s}$) $I_{FGM} = 2 \text{ A}$ ($t_p = 20 \mu\text{s}$) $V_{RGM} = 5 \text{ V}$ $P_G(\text{AV}) = 0.5 \text{ W}$ $V_{FGM} = 15 \text{ V}$ ($t_p = 20 \mu\text{s}$)**ELECTRICAL CHARACTERISTICS**

Symbol	Test Conditions			Min.	Typ.	Max.	Unit
I_{GT}	$T_j = 25^\circ\text{C}$ Pulse Duration > 20 μs	$V_D = 12 \text{ V}$	$R_L = 33 \Omega$			15	mA
V_{GT}	$T_j = 25^\circ\text{C}$ Pulse Duration > 20 μs	$V_D = 12 \text{ V}$	$R_L = 33 \Omega$			1.5	V
V_{GD}	$T_j = 125^\circ\text{C}$	$V_D = V_{DRM}$	$R_L = 3.3 \text{ k}\Omega$	0.2			V
I_H	$T_j = 25^\circ\text{C}$	$I_T = 100 \text{ mA}$	Gate Open			30	mA
I_L	$T_j = 25^\circ\text{C}$ Pulse Duration > 20 μs	$V_D = 12 \text{ V}$	$I_G = 30 \text{ mA}$		50		mA
V_{TM}	$T_j = 25^\circ\text{C}$	$I_{TM} = 24 \text{ A}$	$t_p = 10 \text{ ms}$			1.6	V
I_{DRM}	$T_j = 25^\circ\text{C}$	V_{DRM} Specified				0.01	mA
	$T_j = 125^\circ\text{C}$	$V_{DRM} \leq 800 \text{ V}$				2	
		$V_{DRM} = 1000 \text{ V}$				3	
I_{RRM}	$T_j = 25^\circ\text{C}$	V_{RRM} Specified				0.01	mA
	$T_j = 125^\circ\text{C}$	$V_{RRM} \leq 800 \text{ V}$				2	
		$V_{RRM} = 1000 \text{ V}$				3	
t_{gt}	$T_j = 25^\circ\text{C}$ $I_G = 40 \text{ mA}$	$V_D = V_{DRM}$ $di_G/dt = 0.45 \text{ A}/\mu\text{s}$	$I_T = 24 \text{ A}$		2		μs
t_q	$T_j = 125^\circ\text{C}$ $V_D = 67\% V_{DRM}$ Gate Open	$I_T = 24 \text{ A}$ $di/dt = 30 \text{ A}/\mu\text{s}$	$V_R = 25 \text{ V}$ $dv/dt = 50 \text{ V}/\mu\text{s}$		70		μs
dv/dt^*	$T_j = 125^\circ\text{C}$ Linear Slope up to $V_D = 67\% V_{DRM}$	Gate Open		200			$\text{V}/\mu\text{s}$

* For higher guaranteed values, please consult us.




Fig.1 - Maximum mean power dissipation versus mean on-state current.




Fig.2 - Correlation between maximum mean power dissipation and maximum allowable temperatures (T_{amb} and T_{case}) for different thermal resistances heatsink + contact.




Fig.3 - Mean on-state current versus case temperature.




Fig.5 - Relative variation of gate trigger current and holding current versus junction temperature.




Fig.4 - Thermal transient impedance junction to case and junction to ambient versus pulse duration.




Fig.6 - Non repetitive surge peak on-state current versus number of cycles.




Fig.7 - Non repetitive surge peak on-state current for a sinusoidal pulse with width : $t \leq 10$ ms, and corresponding value of I^2t .





Fig.8 - On-state characteristics (maximum values).

PACKAGE MECHANICAL DATA : TO 220 AB Plastic



Cooling method : by conduction (method C)

Marking : type number

Weight : 2 g