

Marketing Bulletin

7200-RPM Drive Specification Comparison

Selecting the right hard drive is best done when the decision is based on application usage, technology requirements and drive design considerations. The specification information here works in conjunction with the *Drive Selection Guide* (MB538) to help you get a clear understanding of why a particular hard drive works most effectively in the customer's environment. Additionally, our customers and partners need to understand that there is more to a hard drive than just the initial acquisition cost. That's only the starting point of the total ownership cost model.

Choosing the right hard drive means that you are purchasing a product that is optimized, tested, serviced and supported for your specific usage environment. Consideration must be made for ongoing operational and maintenance costs that include power usage and overall drive reliability that impacts service costs like return processing, diagnostics, customer downtime, goodwill, etc. The bottom line: Seagate is in the unique position of having the breadth, experience and infrastructure derived from industry-leading partnerships in all business segments.

If the application is digital video surveillance, recommending Seagate SV35 Series™ drives offers high-capacity, surveillance-optimized solutions for both indoor and outdoor 24x7 digital video and metadata usage. If a customer is looking for a desktop drive, the Seagate Barracuda® products will exceed their expectations. This family of drives is unlike any other in the market today; they have the highest benchmark performance scores and the lowest power consumption. They are optimized for PC and personal storage environments. If customers are looking for enterprise-optimized solutions, considering total cost of ownership, enterprise-class service and support, and Tier 2/capacity-optimized nearline features, the answer is found in the Seagate Constellation® and Seagate Constellation ES product families.

For more information, see the Drive Selection Guide on our partner website to make sure your customers are purchasing the best drives for their unique environments.

7200-RPM Drive Specification Comparison



Specifications	Barracuda®	Constellation®	Constellation ES	SV35 Series™
Primary applications	Optimized for PC and personal external storage	Optimized for 2.5-inch business server and external storage arrays	Optimized for 3.5-inch business server and external storage arrays	Optimized for video surveillance applications
Capacity (GB)	250, 320, 500, 750, 1000 1500, 2000, 3000	250, 500, 1000	500, 1000, 2000, 3000	1000, 2000, 3000
Spin speed (RPM)	7200	7200	7200	7200
SATA interface (Gb/s)	1.5/3.0/6.0	1.5/3.0/6.0	1.5/3.0/6.0	1.5/3.0/6.0
SAS interface (Gb/s)	—	3.0/6.0	3.0/6.0	—
Rotational vibration (RV) (radians/s/s)	5.5 narrow spectrum up to 300Hz	16 broad spectrum up to 1800Hz	12.5 broad spectrum up to 1500Hz	5.5 narrow spectrum up to 300Hz
Seek time, average read/write (ms)	<8.5/<9.5	8.5/9.5	8.5/9.5	<8.5/<9.5
Cache (MB)¹	16, 64	Up to 64	Up to 64	64
Nonrecoverable read errors per bits read	1 sector per 10E14	1 sector per 10E15	1 sector per 10E15	1 sector per 10E14
Power-on hours (POH)	2400–8x5	8760–24x7	8760–24x7	8760–24x7
Streaming capabilities	—	Multiple sequential streams	Multiple sequential streams	Up to 20 simultaneous HD streams ³
POH usage profile	8x5–On as needed	24x7–Always on	24x7–Always on	Up to 64 cameras 24x7–Always on
MTBF (hours)	700,000	1.4 million	1.2 million	1 million
Power, average – idle (W)²	4.6	2.25 to 3.85	>3.74	—
Power, average – idle2 (W)²	3.4 to 5.4	—	—	3.4 to 5.4
Acoustics, typical – idle (bels)	2.2 to 2.4	2.2	1.9 to 2.7	2.2 to 2.4
Shock, operating/nonoperating (Gs)	70 to 80/300 to 350	70/400	40 to 70/300	80/300 to 350
Ambient temperature, operating/nonoperating (Gs)	0 to 60/–40 to 70	5 to 60/–40 to 70	5 to 60/–40 to 70	0 to 70/–40 to 70
RAID support	0, 1	0, 1, 3, 4, 5, 6, 10	0, 1, 3, 4, 5, 6, 10	0, 1, 3, 4, 5, 6, 10
RAID Rebuild™ support		•	•	
Enterprise expert support		•	•	•

¹ Cache size availability varies by capacity points and interface.

² Power consumption varies by capacity points and interface.

³ Streaming capabilities for video surveillance is dependent on customer configuration.

www.seagate.com

AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 16–18 rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2012 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Barracuda, Constellation, RAID Rebuild and SV35 Series are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Seagate reserves the right to change, without notice, product offerings or specifications. MB578.7-1201US, January 2012